F 3 8 A B A R X

SPECIFICATION PROPOSAL

Vehicle Configuration

M2 106 CONVENTIONAL CHASSIS

2018 MODEL YEAR SPECIFIED

TRAILER TOWING PROVISION AT END OF FRAME FOR TRUCK

General Service

TRUCK/TRAILER CONFIGURATION

DOMICILED, USA 50 STATES (INCLUDING CALIFORNIA AND CARB OPT-IN STATES)

TERRAIN/DUTY: 100% (ALL) OF THE TIME, IN TRANSIT, IS SPENT ON PAVED ROADS

MAXIMUM 8% EXPECTED GRADE

SMOOTH CONCRETE OR ASPHALT PAVEMENT - MOST SEVERE IN-TRANSIT (BETWEEN SITES) ROAD

SURFACE

MEDIUM TRUCK WARRANTY

EXPECTED FRONT AXLE(S) LOAD: 12000.0 lbs
EXPECTED REAR DRIVE AXLE(S) LOAD: 21000.0 lbs

EXPECTED GROSS VEHICLE WEIGHT CAPACITY: 33000.0 lbs EXPECTED GROSS COMBINATION WEIGHT: 33000.0 lbs

Engine

CUM B6.7 300 HP @ 2600 RPM, 2600 GOV, 660 LB/FT @ 1600 RPM

Electronic Parameters

85 MPH ROAD SPEED LIMIT

CRUISE CONTROL SPEED LIMIT SAME AS ROAD SPEED LIMIT

PTO MODE ENGINE RPM LIMIT - 1100 RPM

PTO MODE BRAKE OVERRIDE - SERVICE BRAKE ONLY ENABLED

PTO RPM WITH CRUISE SET SWITCH - 700 RPM

PTO RPM WITH CRUISE RESUME SWITCH - $800\ RPM$

PTO MODE CANCEL VEHICLE SPEED - 5 MPH

PTO GOVERNOR RAMP RATE - 250 RPM PER SECOND

PTO MINIMUM RPM - 700

REGEN INHIBIT SPEED THRESHOLD - 0 MPH

Engine Equipment

2016 ONBOARD DIAGNOSTICS/2010 EPA/CARB/GHG14

2008 CARB EMISSION CERTIFICATION - CLEAN IDLE (INCLUDES 6X4 INCH LABEL ON LOWER FORWARD CORNER OF DRIVER DOOR)

SIDE OF HOOD AIR INTAKE WITH FIREWALL MOUNTED DONALDSON AIR CLEANER

DR 12V 160 AMP 28-SI QUADRAMOUNT PAD ALTERNATOR WITH REMOTE BATTERY VOLT SENSE

(2) ALLIANCE MODEL 1131, GROUP 31, 12 VOLT MAINTENANCE FREE 1900 CCA BATTERIES

SINGLE BATTERY BOX FRAME MOUNTED LH SIDE UNDER CAB

WIRE GROUND RETURN FOR BATTERY CABLES WITH ADDITIONAL FRAME GROUND RETURN

NON-POLISHED BATTERY BOX COVER

CUMMINS TURBOCHARGED 18.7 CFM AIR COMPRESSOR WITH INTERNAL SAFETY VALVE

ELECTRONIC ENGINE INTEGRAL SHUTDOWN PROTECTION SYSTEM

CUMMINS EXHAUST BRAKE INTEGRAL WITH VARIABLE GEOMETRY TURBO WITH ON/OFF DASH SWITCH

RH INBOARD FRAME MOUNTED HORIZONTAL AFTERTREATMENT SYSTEM ASSEMBLY WITH HORIZONTAL TAILPIPE

ENGINE AFTERTREATMENT DEVICE, AUTOMATIC OVER THE ROAD REGENERATION AND DASH MOUNTED REGENERATION REQUEST SWITCH

STANDARD EXHAUST SYSTEM LENGTH

RH STANDARD HORIZONTAL TAILPIPE

6 GALLON DIESEL EXHAUST FLUID TANK

HORTON HT650 FRONTAL AIR ON/OFF ENGINE FAN CLUTCH

AUTOMATIC FAN CONTROL WITH DASH SWITCH AND INDICATOR LIGHT, NON ENGINE MOUNTED

CUMMINS SPIN ON FUEL FILTER

FULL FLOW OIL FILTER

950 SQUARE INCH ALUMINUM RADIATOR

ANTIFREEZE TO -34F, OAT (NITRITE AND SILICATE FREE) EXTENDED LIFE COOLANT

GATES BLUE STRIPE COOLANT HOSES OR EQUIVALENT

CONSTANT TENSION HOSE CLAMPS FOR COOLANT HOSES

LOWER RADIATOR GUARD

PHILLIPS-TEMRO 750 WATT/115 VOLT BLOCK HEATER

CHROME ENGINE HEATER RECEPTACLE MOUNTED UNDER LH DOOR

ALUMINUM FLYWHEEL HOUSING

ELECTRIC GRID AIR INTAKE WARMER

DELCO 12V 29MT STARTER WITH INTEGRATED MAGNETIC SWITCH

Transmission

ALLISON 2500 RDS AUTOMATIC TRANSMISSION WITH PTO PROVISION

Transmission Equipment

ALLISON VOCATIONAL PACKAGE RDS

PRIMARY MODE GEARS, 6 FORWARD GEARS WITH MANUAL SELECTION FOR 3, 2 AND 1

CUSTOMER INSTALLED MUNCIE CS6 SERIES PTO WITH ELECTRIC/HYDRAULIC CONTROLS

PTO MOUNTING, LH SIDE OF MAIN TRANSMISSION

MAGNETIC PLUGS, ENGINE DRAIN, TRANSMISSION DRAIN, AXLE(S) FILL AND DRAIN

DASH MOUNTED T-HANDLE CABLE SHIFT CONTROL WITHOUT PARK BRAKE POSITION

WATER TO OIL TRANSMISSION COOLER, IN RADIATOR END TANK

TRANSMISSION OIL CHECK AND FILL

SYNTHETIC TRANSMISSION FLUID (TES-295 COMPLIANT)

Front Axle and Equipment

DETROIT DA-F-12.0-3 12,000# FF1 71.5 KPI/3.74 DROP SINGLE FRONT AXLE

MERITOR 16.5X5 Q+ CAST SPIDER CAM FRONT BRAKES, DOUBLE ANCHOR, FABRICATED SHOES

NON-ASBESTOS FRONT BRAKE LINING

CONMET CAST IRON FRONT BRAKE DRUMS

SKF SCOTSEAL PLUS XL FRONT OIL SEALS

VENTED FRONT HUB CAPS WITH WINDOW, CENTER AND SIDE PLUGS - OIL

MERITOR AUTOMATIC FRONT SLACK ADJUSTERS

TRW THP-60 POWER STEERING

2 QUART SEE THROUGH POWER STEERING RESERVOIR

SYNTHETIC 75W-90 FRONT AXLE LUBE

Front Suspension

12,000# DUAL TAPERLEAF FRONT SUSPENSION

MAINTENANCE FREE RUBBER BUSHINGS - FRONT SUSPENSION

FRONT SHOCK ABSORBERS

Rear Axle and Equipment

MS-21-14X 21,000# R-SERIES SINGLE REAR AXLE

5.29 REAR AXLE RATIO

IRON REAR AXLE CARRIER WITH STANDARD AXLE HOUSING

SPL100 DANA SPICER MAIN DRIVELINE WITH HALF ROUND YOKES

MERITOR 16.5X7 Q+ CAST SPIDER CAM REAR BRAKES, DOUBLE ANCHOR, FABRICATED SHOES

NON-ASBESTOS REAR BRAKE LINING

BRAKE CAMS AND CHAMBERS ON FORWARD SIDE OF DRIVE AXLE(S) WITH AUXILIARY SUPPORT BRACKETS

CONMET CAST IRON REAR BRAKE DRUMS

SKF SCOTSEAL PLUS XL REAR OIL SEALS

HALDEX GOLDSEAL LONGSTROKE 1-DRIVE AXLE SPRING PARKING CHAMBERS

MERITOR AUTOMATIC REAR SLACK ADJUSTERS

SYNTHETIC 75W-90 REAR AXLE LUBE

Rear Suspension

AIRLINER 23,000# REAR SUSPENSION WITH CHAIN CLEARANCE

AIRLINER HIGH POSITION RIDE HEIGHT

STANDARD U-BOLT PAD

MANUAL DUMP VALVE FOR AIR SUSPENSION WITHOUT GAUGE

INDICATOR LIGHT AND BUZZER FOR EACH REAR SUSPENSION CONTROL SWITCH

SINGLE AIR REAR SUSPENSION LEVELING VALVE

TRANSVERSE CONTROL RODS

REAR SHOCK ABSORBERS - ONE AXLE (AIR RIDE SUSPENSION)

Brake System

AIR BRAKE PACKAGE

WABCO 4S/4M ABS WITHOUT TRACTION CONTROL

REINFORCED NYLON, FABRIC BRAID AND WIRE BRAID CHASSIS AIR LINES

FIBER BRAID PARKING BRAKE HOSE

STANDARD BRAKE SYSTEM VALVES

STANDARD AIR SYSTEM PRESSURE PROTECTION SYSTEM

RELAY VALVE WITH 5-8 PSI CRACK PRESSURE, NO REAR PROPORTIONING VALVE

WABCO SS-1200 PLUS AIR DRYER WITH INTEGRAL AIR GOVERNOR AND HEATER

PULL CABLES ON ALL AIR RESERVOIR(S)

Trailer Connections

AIR CONNECTIONS TO END OF FRAME WITH GLAD HANDS FOR TRUCK AND NO DUST COVERS

PRIMARY CONNECTOR/RECEPTACLE WIRED FOR SEPARATE STOP/TURN, CENTER PIN POWERED

SAE J560 7-WAY PRIMARY TRAILER CABLE RECEPTACLE MOUNTED END OF FRAME

UPGRADED CHASSIS MULTIPLEXING UNIT

UPGRADED BULKHEAD MULTIPLEXING UNIT

Wheelbase & Frame

5850MM (230 INCH) WHEELBASE

11/32X3-1/2X10-3/16 INCH STEEL FRAME (8.73MMX258.8MM/0.344X10.19 INCH) 120KSI

CALC'D BACK OF CAB TO REAR SUSP C/L (CA): 138.86 in

FRONT CLOSING CROSSMEMBER

STANDARD WEIGHT ENGINE CROSSMEMBER

STANDARD MIDSHIP #1 CROSSMEMBER(S)

STANDARD REARMOST CROSSMEMBER

HEAVY DUTY SUSPENSION CROSSMEMBER

Chassis Equipment

THREE-PIECE 14 INCH CHROMED STEEL BUMPER WITH COLLAPSIBLE ENDS

FRONT TOW HOOKS - FRAME MOUNTED

FENDER AND FRONT OF HOOD MOUNTED FRONT MUDFLAPS

GRADE 8 THREADED HEX HEADED FRAME FASTENERS

Fuel Tanks

50 GALLON/189 LITER RECTANGULAR ALUMINUM FUEL TANK - RH

50 GALLON/189 LITER SHORT RECTANGULAR ALUMINUM FUEL TANK - LH

POLISHING OF FUEL/HYDRAULIC TANK(S) WITH PAINTED BANDS

BLACK STEP FINISH

ALLIANCE FUEL FILTER/WATER SEPARATOR WITH PRIMER PUMP

EQUIFLO INBOARD FUEL SYSTEM

Tires

MICHELIN XZE2 275/80R22.5 14 PLY RADIAL FRONT TIRES

MICHELIN XDA ENERGY 275/80R22.5 14 PLY RADIAL REAR TIRES

Hubs

CONMET PRE-SET BEARING IRON FRONT HUBS

CONMET PRE-SET BEARING IRON REAR HUBS

Wheels

ALCOA LVL ONE 88367X 22.5X8.25 10-HUB PILOT ALUMINUM DISC FRONT WHEELS

ALCOA LVL ONE ALUMINUM OUTSIDE, STEEL INSIDE; 22.5X8.25 10-HP DISC REAR WHEELS

POLISHED FRONT WHEELS; OUTSIDE ONLY

POLISHED REAR WHEELS; OUTSIDE OF OUTER WHEELS ONLY

Cab Exterior

132 INCH BBC HIGH-ROOF EXTENDED ALUMINUM CONVENTIONAL CAB

AIR CAB MOUNTS

NONREMOVABLE BUGSCREEN MOUNTED BEHIND GRILLE

LH AND RH GRAB HANDLES

HOOD MOUNTED CHROMED PLASTIC GRILLE

CHROMED HOOD MOUNTED AIR INTAKE GRILLE

TUNNEL/FIREWALL LINER

DUAL 26 INCH RECTANGULAR POLISHED ALUMINUM AIR HORNS ROOF MOUNTED

SINGLE ELECTRIC HORN

DUAL HORN SHIELDS

INTEGRAL HEADLIGHT/MARKER ASSEMBLY WITH CHROME BEZEL

LED AERODYNAMIC MARKER LIGHTS

DAYTIME RUNNING LIGHTS

STANDARD FRONT TURN SIGNAL LAMPS

DUAL WEST COAST BRIGHT FINISH HEATED MIRRORS WITH LH AND RH REMOTE

DOOR MOUNTED MIRRORS

102 INCH EQUIPMENT WIDTH

LH AND RH 8 INCH BRIGHT FINISH CONVEX MIRRORS MOUNTED UNDER PRIMARY MIRRORS

STANDARD SIDE/REAR REFLECTORS

DUAL LEVEL CAB ENTRY STEPS ON BOTH SIDES

COMPOSITE EXTERIOR SUN VISOR

63X14 INCH TINTED REAR WINDOW

TINTED DOOR GLASS LH AND RH WITH TINTED OPERATING WING WINDOWS

RH AND LH ELECTRIC POWERED WINDOWS

20X23 INCH LH AND RH TINTED SIDE WINDOWS

TINTED WINDSHIELD

2 GALLON WINDSHIELD WASHER RESERVOIR WITH FLUID LEVEL INDICATOR, FRAME MOUNTED

Cab Interior

OPAL GRAY VINYL INTERIOR

INTERIOR CONVENIENCE PACKAGE

MOLDED DOOR PANEL WITH UPPER VINYL INSERTS

MOLDED DOOR PANEL WITH UPPER VINYL INSERTS

BLACK MATS WITH SINGLE INSULATION

DASH MOUNTED ASH TRAYS AND LIGHTER

FORWARD ROOF MOUNTED CONSOLE WITH UPPER STORAGE COMPARTMENTS AND ADDITIONAL CENTER COMPARTMENT WITHOUT NETTING

IN DASH STORAGE BIN

PLASTIC MANIFEST BOX - LH DOOR

(2) CUP HOLDERS LH AND RH DASH

GRAY/CHARCOAL FLAT DASH

2-1/2 LB. FIRE EXTINGUISHER

HEATER, DEFROSTER AND AIR CONDITIONER

STANDARD HVAC DUCTING

MAIN HVAC CONTROLS WITH RECIRCULATION SWITCH

STANDARD HEATER PLUMBING

DENSO HEAVY DUTY AIR CONDITIONER COMPRESSOR

BINARY CONTROL, R-134A

STANDARD INSULATION

SOLID-STATE CIRCUIT PROTECTION AND FUSES

12V NEGATIVE GROUND ELECTRICAL SYSTEM

DOOR ACTIVATED DOME/RED MAP LIGHTS, FORWARD LH AND RH AND REAR CENTER

LH AND RH ELECTRIC DOOR LOCKS

PREMIUM HIGH BACK AIR SUSPENSION DRIVER SEAT WITH 3 CHAMBER AIR LUMBAR, INTEGRATED CUSHION EXTENSION, FORWARD AND REAR CUSHION TILT, ADJUSTABLE SHOCK ABSORBER

HIGH BACK NON SUSPENSION PASSENGER SEAT

FULL WIDTH REAR BENCH SEAT

DUAL DRIVER SEAT ARMRESTS, NO PASSENGER SEAT ARMRESTS

LH AND RH INTEGRAL DOOR PANEL ARMRESTS

VINYL WITH VINYL INSERT DRIVER SEAT

VINYL WITH VINYL INSERT PASSENGER SEAT

VINYL WITH VINYL INSERT REAR PASSENGER SEAT

3 POINT DRIVER AND FRONT PASSENGER SEAT BELTS; 3 POINT LH AND RH AND 2 POINT CENTER REAR PASSENGER SEAT BELTS

ADJUSTABLE TILT AND TELESCOPING STEERING COLUMN

4-SPOKE 18 INCH (450MM) STEERING WHEEL

DRIVER AND PASSENGER INTERIOR SUN VISORS

Instruments & Controls

WOODGRAIN DRIVER INSTRUMENT PANEL

WOODGRAIN CENTER INSTRUMENT PANEL

BLACK GAUGE BEZELS

LOW AIR PRESSURE LIGHT AND BUZZER

2 INCH PRIMARY AND SECONDARY AIR PRESSURE GAUGES

INTAKE MOUNTED AIR RESTRICTION INDICATOR WITHOUT GRADUATIONS

ELECTRONIC CRUISE CONTROL WITH SWITCHES IN LH SWITCH PANEL

KEY OPERATED IGNITION SWITCH AND INTEGRAL START POSITION; 4 POSITION OFF/RUN/START/ACCESSORY

ODOMETER/TRIP/HOUR/DIAGNOSTIC/VOLTAGE DISPLAY: 1X7 CHARACTER, 26 WARNING LAMPS, DATA LINKED, ICU3

DIAGNOSTIC INTERFACE CONNECTOR, 9 PIN, SAE J1939, LOCATED BELOW DASH

2 INCH ELECTRIC FUEL GAUGE

ELECTRICAL ENGINE COOLANT TEMPERATURE GAUGE

2 INCH TRANSMISSION OIL TEMPERATURE GAUGE

ENGINE AND TRIP HOUR METERS INTEGRAL WITHIN DRIVER DISPLAY

(1) DASH MOUNTED PTO SWITCH WITH INDICATOR LAMP

ELECTRIC ENGINE OIL PRESSURE GAUGE

AM/FM/WB RADIO WITH CD PLAYER, BLUETOOTH AND MICROPHONE, IPOD INTERFACE, AND USB AND FRONT AUXILIARY INPUTS

(2) RADIO SPEAKERS IN CAB

AM/FM ANTENNA MOUNTED ON FORWARD LH ROOF

ELECTRONIC MPH SPEEDOMETER WITH SECONDARY KPH SCALE, WITHOUT ODOMETER

STANDARD VEHICLE SPEED SENSOR

ELECTRONIC 3000 RPM TACHOMETER

IGNITION SWITCH CONTROLLED ENGINE STOP

(6) IGN CONTROLLED EXTRA SWITCHES WITH IND LIGHTS WIRED TO POWER DIST BOX WITH RELAYS PROVIDING 20 AMPS PER CIRCUIT TO JUNCTION BLOCK AND 1 CIRCUIT AT 30 AMPS

BW TRACTOR PROTECTION VALVE

TRAILER HAND CONTROL BRAKE VALVE AND WINCH BRAKE (APPLIES 45 PSI AIR TO STEER AXLE SERVICE BRAKES WHEN PARKED)

DIGITAL VOLTAGE DISPLAY INTEGRAL WITH DRIVER DISPLAY

SINGLE ELECTRIC WINDSHIELD WIPER MOTOR WITH DELAY

MARKER LIGHT SWITCH INTEGRAL WITH HEADLIGHT SWITCH

TWO VALVE PARKING BRAKE SYSTEM WITH WARNING INDICATOR

SELF CANCELING TURN SIGNAL SWITCH WITH DIMMER, WASHERWIPER AND HAZARD IN HANDLE

INTEGRAL ELECTRONIC TURN SIGNAL FLASHER WITH HAZARD LAMPS OVERRIDING STOP LAMPS

Design

PAINT: ONE SOLID COLOR

Color

CAB COLOR A: L0006EB WHITE ELITE BC

BLACK, HIGH SOLIDS POLYURETHANE CHASSIS PAINT

SUNVISOR PAINTED SAME AS CAB COLOR A

Certification / Compliance

U.S. FMVSS CERTIFICATION

Secondary Factory Options

CORPORATE PDI CENTER IN-SERVICE ONLY

Extended Warranty

TOWING EXTENDED/ROADSIDE SERVICE WARRANT 05/24/10 Y, 1 YEAR/UNLIMITED MILES/KM, \$550 CAP

CUM 2017 B6.7: HD1 5 Years / 300,000 Miles EXTENDED WARRANTY.

CUM 2017 B6.7: AT3 MD DTY 5 Years / 300,000 Miles AFTERTREATMENT

QUOTATION

M2 106 CONVENTIONAL CHASSIS

SET BACK AXLE - TRUCK

CUM B6.7 300 HP @ 2600 RPM, 2600 GOV, 660 LB/FT @ 1600 RPM

ALLISON 2500 RDS AUTOMATIC TRANSMISSION WITH PTO PROVISION

MS-21-14X 21,000# R-SERIES SINGLE REAR AXLE AIRLINER 23,000# REAR SUSPENSION WITH CHAIN CLEARANCE DETROIT DA-F-12.0-3 12,000# FF1 71.5 KPI/3.74 DROP SINGLE FRONT AXLE

12,000# DUAL TAPERLEAF FRONT SUSPENSION

132 INCH BBC HIGH-ROOF EXTENDED ALUMINUM CONVENTIONAL CAB

5850MM (230 INCH) WHEELBASE

11/32X3-1/2X10-3/16 INCH STEEL FRAME

(8.73MMX258.8MM/0.344X10.19 INCH) 120KSI

			PER UNIT		TOTAL
VEHICLE PRICE	TOTAL # OF UNITS (2)	\$			
CUSTOMER PRICE BEFORE TAX		\$		\$	
TAXES AND FEES					
TAXES AND FEES		\$	0	\$	0
OTHER CHARGES		\$	0	\$	0
TRADE-IN					
TRADE-IN ALLOWANCE		\$	(0)	\$	(0)
BALANCE DUE	(LOCAL CURRENCY)	\$		\$	
APPROVAL:					
Please indicate your acceptance of this quotation by signing below:					
Customer: X	Date: /	/			