



MHC Kenworth - Chattanooga T652  
7831 LEE HIGHWAY

ZTE  
316 W MILWAUKEE ST

CHATTANOOGA, Tennessee United States 37421  
Phone: (423) 698-4461  
Fax:  
Email:

NEW HAMPTON, Iowa United States 50659  
Phone: (800) 444-5454  
Fax:  
Contact Email:  
Prepared for:

### Vehicle Summary

	Unit	Chassis	
Model:	T270 Series Conventional	Fr Axle Load (lbs):	10000
Type:	FULL TRUCK	Rr Axle Load (lbs)	16000
Description:	ZTE T270 CA84	G.C.W. (lbs):	26000
	<b>Application</b>	Road Conditions:	
Intended Serv.:	Local pickup & delivery.	Class A (Highway)	90
	Vehicles which haul	Class B (Hwy/Mtn)	10
Commodity:	Auto transporter	Class C (Off-Hwy)	00
	<b>Body</b>	Class D (Off-Road)	00
Type:	Roll back flatbed	Maximum Grade:	6
Length (ft):	22.0	Wheelbase (in):	162
Height (ft):	12.0	Overhang (in):	64
Max Laden Weight (lbs):	4000	Fr Axle to BOC (in):	68
	<b>Trailer</b>	Cab to Axle (in):	94
No. of Trailer Axles:	0	Cab to EOF (in):	158
Type:		Overall Comb. Length (in):	267
Length (ft):	0.0		
Height (ft):	0.0	<b>Special Req.</b>	
Kingpin Inset (in):	0	U.S. Domestic Registry, 50-State	
Corner Radius (in):	0		
	<b>Restrictions</b>		
Length (ft):	120		
Width (in):	102		
Height (ft):	13.5		

Approved by: \_\_\_\_\_

Date: \_\_\_\_\_

**Note: All sales are F.O.B. designated plant of manufacture.**

	Ask your dealer for a quote today, or visit our website @ <a href="http://www.paccarfinancial.com">www.paccarfinancial.com</a> .
	PACCAR Financial offers innovative finance, lease and insurance programs customized to meet your needs.

Unpublished options may require review/approval.  
Dimensional and performance data for unpublished options may vary from that displayed in PROSPECTOR.

Printed:	2/15/2018 12:16:10 PM	<b>Complete</b>	Model Number:	T270 Series Conventional
Effective Date:	Jul 1, 2017		Quote/DTPO/CO:	Q01565391
Prepared by:	ID: jervin		Version Number:	40.30



MHC Kenworth - Chattanooga T652  
7831 LEE HIGHWAY

ZTE  
316 W MILWAUKEE ST

CHATTANOOGA, Tennessee United States 37421  
Phone: (423) 698-4461  
Fax:  
Email:

NEW HAMPTON, Iowa United States 50659  
Phone: (800) 444-5454  
Fax:  
Contact Email:  
Prepared for:

Model	Description	Weight
	<b>T270 Series Conventional</b> Electric Door locks LH/RH; Ignition & doors keyed alike; Single electric horn; Single-piece windshield; Electric windshield wipers, 2-speed plus intermittent; Electric windshield washers; Steering wheel 18in. 4-spoke; Glovebox door with locking latch; Dash-mounted cruise control with switches; Turn signal switch with column-mounted dimmer; Standard dash panels include gray w/ burl wood accents; Slate Gray interior primary color; Dark Slate Gray seat color; Floor mat; Inside sunvisor, LH/RH; Door courtesy lights; Under-dash center console with 1 cup holder, 1 ashtray & 1 lighter.	9,514
	<b>T270 Class 6: medium-duty Conventional.</b>	0
	<b>CARB Idle Emissions Reduction Feature for PX-7 and PX-9</b>	0
	<b>Class 6 4x2 automatic.</b>	0
	<b>Auto transporter</b>	0
	<b>Local pickup &amp; delivery. Vehicles which haul freight, typically operating within a 100-mile radius, on public streets &amp; highways, &amp; other paved surfaces, including limited Class C roads. Includes package &amp; freight delivery, as well as fuel oil or petroleum distribution, etc. Road usage: minimum 3% Class B, do not code for Class D.</b>	0
	<b>Roll back flatbed</b>	0
	<b>U.S. Domestic Registry, 50-State</b>	0

**Engine & Equipment**

<b>PACCAR PX-7 300 2017 300@2600 660@1600</b>	0
Includes turbo exhaust brake, no code is used. Diagnostic Plug for data link, Oil Cooler, Aluminum Flywheel Housing.	
N09200 N205 120..Standard Maximum Speed Limit [LSL]	
N09220 N207 0...Expiration Distance	
N09240 P09 120...Hard Maximum Speed Limit	
N09260 P14 82...Maximum Accelerator Pedal Vehicle Speed	
N09280 P16 0...Accelerator Lower Droop	
N09300 P19 82...Maximum Cruise Speed	
N09320 C143 0...Cruise Control Lower Droop	
N09360 N203 252..Reserve Speed Function Reset Distance	
N09380 N202 0...Maximum Cycle Distance	
N09400 N206 10...Maximum Active Distance	
N09420 N201 0...Reserve Speed Limit Offset	

Unpublished options may require review/approval.  
Dimensional and performance data for unpublished options may vary from that displayed in PROSPECTOR.

Printed:	2/15/2018 12:16:10 PM	<b>Complete</b>	Model Number:	T270 Series Conventional
Effective Date:	Jul 1, 2017		Quote/DTPO/CO:	Q01565391
Prepared by:	ID: jervin		Version Number:	40.30

Description	Weight
N09440 P11 YES..Engine Protection Shutdown	
N09460 P06 NO...Gear Down Protection	
N09480 P26 1150.Max PTO Speed	
N09500 P02 NO...Cruise Control Auto Resume	
N09520 P04 NO...Auto Engine Brake in Cruise	
N09540 N209 0....Expiration Distance	
N09560 P520 YES..Enable Idle Shutdown Park Brake Set	
N09580 P32 5....Timer Setting	
N09600 P233 YES..Enable Impending Shutdown Warning	
N09620 P234 60...Timer For Impending Shutdown Warning	
N09640 P516 35...Engine Load Threshold	
N09680 P33 NO...Idle Shutdown Manual Overrule	
N09720 P230 YES..Enable Hot Ambient Automatic Overrule	
N09740 P46 40...Low Ambient Temperature Threshold	
N09760 P56 60...Intermediate Ambient Temperature Threshold	
N09780 P47 80...High Ambient Temperature Threshold	
<b>Prospector version 39.0</b>	0
Replaces version 38.2	
<b>Effective VSL Setting NA</b>	0
<b>Engine Idle Shutdown Timer Disabled</b>	0
<b>Enable EIST Ambient Temp Overrule</b>	0
<b>Eff EIST NA Expiration Miles</b>	0
Use only with MX and Cummins engines	
<b>Air compressor: Cummins 18.7 CFM For Cummins And PACCAR PX engines.</b>	0
<b>Air Cleaner: Dry-type firewall mounted w/filter restriction indicator.</b>	0
<b>Fan Hub: Horton 2-Speed for PX-7</b>	0
<b>Cooling module: 1000 square inches</b>	0
T170/T270/T370/T470. Includes metal surge tank on T170/T270/T370.	
<b>Bug screen: Front of grille on C500 ,T800, T880, and W900. Behind grille on T660, T680, and T300 (Medium Duty).</b>	2
<b>Exhaust: 2017 EPA Horizontal Under Rail</b>	0
DPF/SCR for PX-7 w/ Horizontal Tailpipe Below RH Rail, BOC.	
<b>Short diffuser used W/Horizontal exhaust</b>	0
<b>Fuel Filter:PACCAR Standard Service Interval</b>	0
Fuel/Water Separator. 2017 Emissions	
<b>Run Aid:None</b>	0
*For Fuel Filter	
<b>Start Aid:12V Heat</b>	1
*For Fuel Filter	
<b>Engine block heater plug mounted LH fender bracket.</b>	0
<b>Block heater, PACCAR 1750 watt 120V for PX-6 and PX-7, 1000 watt for PX-8 and PX-9 or ISL9 engines .</b>	2

Unpublished options may require review/approval.  
Dimensional and performance data for unpublished options may vary from that displayed in PROSPECTOR.

Printed:	2/15/2018 12:16:10 PM	<b>Complete</b>	Model Number:	T270 Series Conventional
Effective Date:	Jul 1, 2017		Quote/DTPO/CO:	Q01565391
Prepared by:	ID: jervin		Version Number:	40.30



Description	Weight
<b>Alternator: 160 amp brush type T3</b>	0
<b>Batteries: 2 PACCAR GP31 threaded post (700-730)</b> 1400-1460 CCA dual purpose.	0
<b>Starter: PACCAR 12 volt electrical system. W/</b> centralized power distribution incorporating plug-in style relays. Circuit protection for serviceability, 12-volt light system w/circuit protection circuits number & color coded.	0
<b>Battery disconnect switches 2, mounted in cab</b> Requires battery box LH under.	0
<b>Multi-function engine connector for body builder</b> interface for Cummins.	0
<b>Body Builder Control Harness coiled EOF for</b> customer installed remote throttle and remote PTO controls. Harness includes Remote PTO control and Remote Throttle controls. T680/T880 models do not require 12-way engine connector sales codes. All other models require (1900082 or 1900084).	2
<b>Transmission &amp; Clutch</b>	
<b>Transmission: Allison 2500RDS 6-speed</b> w/PTO drive gear. 5th Gen controls. Includes heat exchanger. Rugged Duty Series for vocational applications. Transynd transmission fluid is standard on all Allison 1000, 2000, 3000 & 4000 series transmissions.	0
<b>Driveline: 3 Dana standard-duty; 2 centerbearing.</b> *Standard duty is 1710 series.	169
<b>Torque converter included w/Allison</b> Transmission.	0
<b>Left hand Pto access, RH dip stick tube</b>	0
<b>Delete Allison FuelSense</b>	0
<b>J1939 Park Brake Auto Neutral</b>	0
<b>Chassis will be fitted w/ LH trans PTO</b>	0
<b>Chassis will be fitted w/RH trans PTO</b>	0
<b>Front Axle &amp; Equipment</b>	
<b>Dana Spicer E-1002IL Front Axle rated 10K</b> 3-1/2in. drop. Use w/ air brakes only.	-52
<b>Front brakes included w/ front hub package.</b>	0
<b>Air Brake: 14,600 lb. package includes</b> Bendix 16-1/2 x5 brakes, cast drums, aluminum 10-bolt hub pilot LMS hubs, hubcaps, oil seals & automatic slack adjusters. For use w/ 22-1/2in. wheels.	48
<b>Front Springs: Taperleaf 10K w/ shock absorbers</b> for use on 2010+ chassis w/ 22.5in. wheels only.	0
<b>Single power steering gear: 13.2K for air brakes.</b>	0

**Unpublished options may require review/approval.**  
**Dimensional and performance data for unpublished options may vary from that displayed in PROSPECTOR.**

Printed:	2/15/2018 12:16:10 PM	<b>Complete</b>	Model Number:	T270 Series Conventional
Effective Date:	Jul 1, 2017		Quote/DTPO/CO:	Q01565391
Prepared by:	ID: jervin		Version Number:	40.30



	Description	Weight
<b>Rear Axle &amp; Equipment</b>		
	<b>Single Dana Spicer P22060S single reduction rear</b>	0
	<b>Rear Axle Ratio - 5.57.</b>	0
	<b>Single rear brakes included w/rear hub package.</b>	0
	<b>23K air brake package includes 16-1/2x7 in. brakes, cast drums, aluminum 10-bolt hub pilot LMS hubs, automatic slack adjusters and oil seals for use w/ 22.5 in. wheels.</b>	0
	<b>Spring Brake: 3030 high output single.</b>	2
	<b>Bendix 4S/4M anti-lock brake system w/ air traction control (ATC).</b>	2
	<b>Rear suspension: single Hendrickson HAS210L 21K.</b> Welded steel crossmember and gussets w/shocks at 8.3 in. laden height, 8.5 in. unladen height. Medium-duty. Includes air suspension dump valve. Not rear air disc brake compatible.	-121
	<b>Dual leveling valves for single air suspension.</b> Dual leveling valves on single rear suspensions on only available on Neway ADZ for class 8 or Hendrickson HAS for medium duty. Dual leveling valves will not be approved on any other suspensions on T3.	0
<b>Tires &amp; Wheels</b>		
	<b>Front Tires: Goodyear Endurance RSA 11R22.5 16PR</b>	7
	<b>Rear tires: Goodyear G182 RSD11R22.5 14PR</b> 42.1 in. diameter, all position. 19.6 in. SLR. Code is priced per pair of tires.	52
	<b>Rear Tire Quantity: 4</b>	0
	<b>Front Wheel: Kenworth 7-spoke 88768</b> 22.5x8.25 aluminum with Lvl One [TM] finish, hub-pilot mount. 7300lb. maximum rating. Level 1 finish. Air disc brake compatible.	-42
	<b>Rear Wheel: Kenworth 7-spoke 88768</b> 22.5x8.25 aluminum with Lvl One [TM] finish, hub-pilot mount. 7300 lb. maximum rating. Air disc brake compatible. Code is priced per pair of wheels. Level 1 finish.	-84
	<b>Rear Wheel/Rim Quantity: 4</b>	0
<b>Frame &amp; Equipment</b>		
	<b>Frame Rails: 10-5/8 x 3-1/2 x 5/16 in. Steel to 308 in.</b> Truck frame weight is 2.91 lb.-in. per pair of rails. Section modulus is 14.80 cu.in., RBM is 1,776,000 in.-lbs per rail. 120,000 PSI yield. Heat treated. Frame rail availability may be restricted based upon application, axle/suspension capacity, fifth wheel setting, or component/dimensional specifications. The results of the engineering review may result in a change to the requested frame rail. If a change is required Kenworth Application Engineering will advise the dealer of the appropriate material specification for a substitute rail.	76
	<b>Bumper: Aerodynamic Chrome Requires a bumper setting code.</b>	0
	<b>40.9 in. Bumper setting. Requires a bumper code.</b>	0

**Unpublished options may require review/approval.  
Dimensional and performance data for unpublished options may vary from that displayed in PROSPECTOR.**

Printed:	2/15/2018 12:16:10 PM	<b>Complete</b>	Model Number:	T270 Series Conventional
Effective Date:	Jul 1, 2017		Quote/DTPO/CO:	Q01565391
Prepared by:	ID: jervin		Version Number:	40.30



Description	Weight
<b>Removable Front Tow Hooks: 2.</b>	15
<b>Front mudflaps.</b>	0
<b>Battery box: Narrow steel parallel under cab</b> with aluminum diamond plate cover with step. LH under cab. Battery box is 150 mm narrower than the standard battery box. Use with two or three batteries and small round DEF tank LH under cab. Air tanks will be frame mounted. Air dryer must be frame mounted or under the hood. Use with RH under exhaust.	-25
<b>Battery box location: LH Side.</b>	0
<b>Welded Steel Crossmembers: Center and Rear Frame.</b> Standard crossmember.	0
<b>Class 6 26K GVWR, for air brakes only.</b> Requires	0
<b>Square end-of-frame w/o crossmember; non-towing.</b>	0

### Fuel Tanks & Equip

<b>Fuel Tank: 75 US gallon 24.5in. aluminum under</b> replace. Class 8 fuel tanks w/o locking caps include an anti-siphon device on the filler neck.	-16
<b>Small round DEF tank. 11 gallons of</b> useable volume. The DEF tank will be located on the side you specified. If you have specific configuration or body builder concerns, please utilize the Custom Frame Layout option. Standard capacity is calculated by fuel capacity of the vehicle and will accommodate two diesel fill-ups for every DEF fill-up. For 1:1 DEF fuel fill ratio, add 7889204.	0
<b>Fuel Tank Steps: 6in. wide upper &amp; lower F/1 RH</b> under round tank 24.5in. NFPA Compliant. Includes fuel tank crossbrace.	8
<b>Polish only one aluminum tank.</b>	0
<b>Polished cover for 1 DEF tank any size.</b>	3
<b>Polished stainless steel tank straps for 1 tank.</b>	0
<b>Standard DEF to fuel fill ratio: 2:1 or greater.</b>	0
<b>DEF tank location is on the LH.</b>	0
<b>Location: 75 gal fuel tank RH under cab</b>	0

### Cab & Equipment

<b>Cab: Curved Glass Conventional.</b> Cab Includes aluminum & fiberglass fully hucked cab w/ all aluminum bulkhead doors & continuous stainless steel piano-style door hinges. Single electric horn standard. Incandescent exterior lights include diagnosable bulb detection and warning. Trailer cable on tractors includes integrity detection. Standard features include multiplex wiring for interior lights, automated pre-trip inspection, short and open check diagnostics. Warning alarm will sound when lights are left on.	0
---	---

**Unpublished options may require review/approval.  
Dimensional and performance data for unpublished options may vary from that displayed in PROSPECTOR.**

Printed:	2/15/2018 12:16:10 PM	<b>Complete</b>	Model Number:	T270 Series Conventional
Effective Date:	Jul 1, 2017		Quote/DTPO/CO:	Q01565391
Prepared by:	ID: jervin		Version Number:	40.30



Description	Weight
<b>Hood: Sloped aerodynamic hood includes</b> grill & separate bumper.	0
<b>Cab heater: W/integral defrosters &amp; A/C 45,000</b> btu cab heater. No sleeper heater/AC. Includes 5 mode rotary control. T660 include filter media.	0
<b>Adjustable telescoping tilt steering column.</b>	10
<b>Switch &amp; Wiring for Customer-Installed PTO.</b> Electric over hydraulic PTO. Includes switch guard. Wiring is routed to LH frame for connection to the customer installed PTO. No air controls are provided with this code.	0
<b>Information for customer-installed PTO</b> Chelsea 230 Series, 6-bolt	0
<b>Three spare switches: Wired to power.</b>	0
<b>Gauge: 2 air suspension pressure gauges. For use</b> w/air suspension w/dual leveling valves.	0
<b>KW Driver Information Center: Includes fuel</b> economy, RPM display, trip information, truck information, diagnostics, gear display, alarm clock.	0
<b>Instrument package: Includes speedometer,</b> tachometer, fuel gauge, engine coolant temperature gauge, engine oil pressure, voltmeter. Class 8 also includes primary & secondary air reservoir gauges & an air application gauge. DEF level gauge and warning lamp are included with 2010+ engines. Engine hour meter and outside air temperature readouts are standard. Primary read out will be MPH. Add 8240620 to switch primary scale to KPH in Canada.	0
<b>Cab interior: Pinnacle. Includes vinyl headliner</b> & cab back panel, slate gray interior, dark slate gray seats, floormats, LH/RH inside sunvisor & door courtesy lights.	0
<b>Driver seat: Kenworth Air cushion Plus HB vinyl.</b> Standard features includes 7 in. fore and aft slide adjustment w/isolator, 6- 23 degree recline, air suspension with cover, dual armrests, and single chamber air lumbar support. Seat cushion is 20 inches wide w/ 2-position tilt and 2-position front cushion extension. Seat material has a horizontal stitch pattern and is 2-tone in color. Seat back is carpeted and includes a map pocket. Seat is manufactured by National. Includes inside visor and retractable 3-point matching seat belts. Grey seat belts.	2
<b>Rider seat: Kenworth Toolbox Plus IB vinyl.</b> W/dual armrests.	-4
<b>Seat color: All Jet Black.</b>	0
<b>Kenworth Radio with AM/FM/WB/USB and Bluetooth</b>	4
<b>Dash mounted CB assembly: W/leads &amp; antennas.</b> Includes dual antenna leads & dual antennas.	4
<b>Under-dash center console: W/2 cup holders, 1</b> ashtray, 1 lighter, 1 12V outlet & a storage compartment.	0
<b>Dome lamp over driver door.</b>	0

Unpublished options may require review/approval.  
Dimensional and performance data for unpublished options may vary from that displayed in PROSPECTOR.

Printed:	2/15/2018 12:16:10 PM	<b>Complete</b>	Model Number:	T270 Series Conventional
Effective Date:	Jul 1, 2017		Quote/DTPO/CO:	Q01565391
Prepared by:	ID: jervin		Version Number:	40.30



Description	Weight
<b>Self cancelling turn signal: W/head light dimmer switch .</b>	0
<b>Cab access contoured grabhandles, LH/RH.</b>	0
<b>Grabhandle: LH inside door frame above dash.</b>	0
<b>Grabhandle: RH inside door frame above dash.</b>	2
<b>Daylite Door: LH/RH includes RH peeper window</b>	0
<b>Dual rectangular air horn 23 in. LH &amp; RH top of roof. Includes air horn covers.</b>	11
<b>Look-Down, Pass. Door, Stainless 8.5x4.4</b>	0
<b>Mirror: Dual Kenworth aerodynamic heated</b> motorized 7 in. x 13 in. mirror w/ chrome shell. LH/RH convex mirrors 5 in. x 7 in. heated. Mirror brackets set for 8 1/2 ft load width. Switch located on door pad.	26
<b>Electric-powered LH &amp; RH door window lifts.</b> Switch located on door.	0
<b>Two corner &amp; one rear cab stationary windows</b> 17.5 in. x 16 in. (two) & 17 in. x 36 in. (one).	24
<b>Exterior stainless steel sunvisor.</b>	11
<b>Lights &amp; Instruments</b>	
<b>Headlamps: Halogen Projector Low Beam, Halogen</b> Complex Reflector High Beam	0
<b>Marker Lights: Five, rectangular, LED</b>	0
<b>Turn Signal Lights: Mounted on fender</b>	0
<b>Combination Stop, Tail, Turn &amp; Backup Lights RH &amp; LH.</b>	0
<b>Body Builder Lighting Harness Coiled End Of Frame</b> For Additional Customer Installed Exterior Lighting. Harness Includes Circuits for Additional Customer Installed Tail Lamps, Turn Lamps, Stop Lamps, and Marker Lamps.	0
<b>Circuit Brakers: Replacing fuses. Does not</b> apply to any 5-amp fuse box position. Brakers include stop/brake/turn, tail lamp, high & low beams, marker/clearance lamps, horn, fuel heat, gauges, air dryer, HVAC controls, panel lamps. Some circuits will remain fuses.	0
<b>Air Equipment</b>	
<b>Air dryer: Bendix AD-SP heated.</b> With 2010 engine installations the dryer is mounted under the hood.	0
<b>Extended Warranty</b>	
<b>Base Warranty - PACCAR PX-7 Engine</b> 36 months / Unlimited miles & km / Unlimited hours.	0

Unpublished options may require review/approval.  
Dimensional and performance data for unpublished options may vary from that displayed in PROSPECTOR.

Printed:	2/15/2018 12:16:10 PM	<b>Complete</b>	Model Number:	T270 Series Conventional
Effective Date:	Jul 1, 2017		Quote/DTPO/CO:	Q01565391
Prepared by:	ID: jervin		Version Number:	40.30





Description	Weight
<b>Base Warranty - Standard Service Medium Duty</b> 12 months / Unlimited miles & km	0
<b>MILLER IND BASE VEHICLE WARRANTY: 3YR/1</b> 50K	0
<b>PACCAR PX-7 EW: PP1,2017 5 YR/300K 482,804 km</b> Each code registered between 366 and 546 days after the vehicle's in-service date will be subject to a \$400 late fee. Coverage cannot be added after 200,000 miles or 545 days past the in-service date.	0
<b>PACCAR PX-7 EW:Aftertreat.,W/PP1 2017 5YR/300K mi</b> 482,804 km. Each code registered between 366 and 546 days after the vehicle's in-service date will be subject to a \$400 late fee. Coverage cannot be added after 200,000 miles or 545 days past the in-service date.	0
<b>Miscellaneous</b>	
<b>Ship to Multiple Locations - Shipping Spreadsheet</b> If your fleet is being shipped to multiple locations, you have 3 days (GRACE) from order entry to send your shipping spreadsheet to your Sales Coordinator.	0
<b>GHG Secondary Manufacturer: Does Not Apply</b>	0
<b>Additional lead time required for off highway &amp;</b> /or specialty component truck.	0
<b>Paint</b>	
<b>Paint color number.</b> N97020 A - L0006 WHITE N97200 FRAME N0001 BLACK	0
<b>Bumper Unpainted</b>	0
<b>Day Cab Standard Paint</b>	0
<b>1 - Color Paint - Day Cab</b> Color will be White if no other color is specified.	0
<b>Base coat/clear coat.</b> The Kenworth Color Selector contains additional instructions, as well as information on Kenworth paint guidelines and surface finish applications. Kenworth is standard with Dupont Imron Elite paint.	0
Total Weight	9653 lb

**Prices and Specifications Subject to Change Without Notice.**

Unpublished options may require review/approval.  
Dimensional and performance data for unpublished options may vary from that displayed in PROSPECTOR.

Printed:	2/15/2018 12:16:10 PM	<b>Complete</b>	Model Number:	T270 Series Conventional
Effective Date:	Jul 1, 2017		Quote/DTPO/CO:	Q01565391
Prepared by:	ID: jervin		Version Number:	40.30