Tow inspection time will be here before you know it. Whether you are looking to finish outfitting one truck or a whole fleet Zip's AW Direct has you covered with all the parts you need to stay compliant.

California Vehicle Code Requirements.

	Current Registration	4000 VC	
	Headlights	24400 VC	
	Beam Indicator	24408 VC	
	Taillamps	24600 VC	Shop Now
	License Plate Lamp	24601 VC	Shop Now
	Stop Lamps	24603 VC	Shop Now
	Rear Lamps w/Cord	24605 VC	Shop Now
	Backup Lamps (1969+)	24606 VC	Shop Now
	Reflectors, Rear	24607	Shop Now
	Reflectors, Front and Side (1968+)	24608 VC	Shop Now
	Turn Signals	24951 VC	Shop Now
	Clearance Lamps (>80"W)	25100 VC	Shop Now
	Amber Warning Lights	25253 VC	Shop Now
	Warning Devices (Reflectors)	25300 VC	Shop Now
	Service Brakes	26311 VC	
	Parking Brake	26451 VC	Shop Now
	Windshield	26700 VC	
	Windshield Wipers	26706 VC	
	Mirrors	26709 VC	Shop Now
	Horn	27000 VC	Shop Now
	Exhaust System	27150 VC	
	Fuel Can	27155 VC	Shop Now
	Tire Tread	24606 VC	
	Fenders/Mud Guards	27600 VC	Shop Now
	Broom	27700 VC	Shop Now
	Shovel	27700 VC	Shop Now
	Fire Extinguisher 4B, C Rating	27700 VC	Shop Now
	Safety Chains	29004 VC	Shop Now
	Signs	27907 VC	Shop Now

Service and other equipment.

	Flashlight	Shop Now
	Wrecking Bar (Large Pry Bar)	Shop Now
	Equivalent of Six 30-Minute Flares	Shop Now

	Trash Cans w/Absorbent	Shop Now
	Shop Rags/Paper Towels	Shop Now
	Shop to Truck Communications (Not a CB radio)	
	Fuel in Approved Containers (Classes A and B)	Shop Now
	Booster Battery or Hot Box	Shop Now
	Hydraulic Jack	Shop Now
	Metric and Standard Lug Wrenches	Shop Now
	Rubber Mallet/Hub Cap Tool	Shop Now
	Lockout Tools (Classes A and B)	Shop Now
	Motorcycle Straps (Class A)	Shop Now
	Sledgehammer	Shop Now
	Tool Kit	Shop Now

Towing Equipment.

	Rating Plates	Shop Now
	Controls Labeled	Shop Now
	Wrecker Boom Assembly	Shop Now
	Wheel Lift Assembly	Shop Now
	Mounting Bolts	
	Winch:	Type:
	Wrecker Controls	Shop Now
	Throttle Control	Shop Now
	Hydraulic Rams, Hoses, Valves	
	Cable Sheaves	Shop Now
	Recovery Chain	Shop Now

Wheel Lift.

	Pivot Pin	Shop Now
	Wheel Tie Down Straps	Shop Now
	"L" Bars	Shop Now
	Cradle/Straps	Shop Now
	Grid/Fork	Shop Now
	Claw	

Conventional.

	Tow Sling	Shop Now
	Sling Pads	Shop Now

Car Carrier.

	Carrier Bed Frame	Shop Now
	Bed Hinges	Shop Now
	Slide Pads	Shop Now
	Bed Safety Lock	Shop Now
	Loading Bridle	Shop Now

Vehicle Safety.

		Steering
		Frame
	Suspension	
	Wheels	

Tow Truck Equipment Specifications (By Class) Class A.

	Minimum 14,000 lbs. GVWR Chassis		
	4-Ton Recovery Equipment Rating		
	One 4-Ton Snatch Block		Shop Now
	Tow Dolly		Shop Now
	Steering Wheel Securement Device		Shop Now
	Wheel Lift Safety Straps		Shop Now
	Tow Sling 3,000 lbs. (If equipped)		Shop Now
	Tow Chains 5/16" Alloy with J/T Hooks	Shop Now	
	Safety Chains 5/16" Alloy or OEM Specifications	Shop Now	
	4Wheel Lift Rating - Extended 3,000 lbs.		
	48"L x 4"W x 4"D & 60"L x 4"W x 4"D Wood Crossbeams		
	100'L x 3/8" dia. Cable 6 x 19 Construction or OEM Specifications	Shop Steel	Shop Fiber

Tow Truck Equipment Specifications (By Class) Class A Car Carrier One Vehicle.

	Minimum 14,000 lbs. GVWR Chassis		
	50'L x 3/8" dia. Cable 6 x 19 Construction or OEM Specifications	Shop Steel	Shop Fiber
	J/T Hook Loading Bridle Chains	Shop Now	
	4 Safety Chains 5/16" Alloy or OEM Specs.		Shop Now
	48"L x 4"W x 4"D & 60"L x 4"W x 4"D Wood Crossbeams		

Class A Car Carrier Two Vehicle.

	Minimum 16,001 lbs. GVWR Chassis		
	J/T Hook Loading Bridle Chains	Shop Now	
	50'L x 3/8" dia. Cable 6 x 19 Construction or OEM Specifications	Shop Steel	Shop Fiber
	4 Safety Chains 5/16" Alloy or OEM Specs. & 2 for Towed Vehicle		Shop Now
	Steering Wheel Securement Device		Shop Now
	48"L x 4"W x 4"D & 60"L x 4"W x 4"D Wood Crossbeams		

Class B.

	Minimum 19,501 lbs. GVWR Chassis		
	14-Ton Recovery Equipment Rating		
	150'L x 7/16" dia. Cable 6 x 19 Construction or OEM Specifications	Shop Steel	Shop Fiber
	Safety Chains 1/2" Alloy or OEM Specifications	Shop Now	

	Two 8-Ton Snatch Blocks	Shop Now	
	Air Brakes or Hydraulic w/Air Hookup Package		
	Air Hoses and Fittings	Shop Now	
	Steering Wheel Securement Device	Shop Now	
	Axle Covers/Caps	Shop Now	
	Tow Sling 7,000 lbs. Rating (If Equipped)		
	48"L x 4"W x 4"D & 60"L x 4"W x 4"D Wood Crossbeams		
	Tow Chains 1/2" Alloy or OEM Specifiations		Shop Now
	Wheel Lift Rating — Retracted 10,000 lbs.		
	Wheel Lift Rating — 85" Extension 8,000 lbs.		
	Wheel Lift Safety Straps		Shop Now
	Lift/Fork Adapters		Shop Now
	Safety Tie-Down Chains		Shop Now
	Aluminum Tow Angles		Shop Now
	Tow Bar 7,000 lbs. Rating		Shop Now

Class B Car Carrier One Vehicle.

	Minimum 19,501 lbs. GVWR Chassis		
	50'L x 3/8" dia. Cable 6 x 19 Construction or OEM Specifications	Shop Steel	Shop Fiber
	J/T Hook Loading Bridle Chains	Shop Now	
	Steering Wheel Securement Device	Shop Now	
	48"L x 4"W x 4"D & 60"L x 4"W x 4"D Wood Crossbeams		
	4 Safety Chains 5/16" Alloy or OEM Specs. & 2 for Towed Vehicle		Shop Now

Class C.

	Minimum 33,000 lbs. GVWR Chassis		
	25-Ton Recovery Equipment Rating		
	200'L x 5/8" dia. Cable 6 x 19 Construction or OEM Specifications	Shop Steel	Shop Fiber
	Safety Chains 5/8" Alloy or OEM Specification	Shop Now	
	Two 12-Ton Snatch Blocks	Shop Now	
	Air Brakes w/Air Hookup Package		
	Air Hoses and Fittings	Shop Now	
	Steering Wheel Securement Device	Shop Now	
	Axle Covers/Caps	Shop Now	
	Tow Sling with 12,000 lbs. Rating (If Equipped)		
	Tow Chains 5/8" Alloy or OEM Specifiactions		Shop Now
	48"L x 4"W x 4"D & 60"L x 4"W x 4"D Wood Crossbeams Pintle Hook		
	Under Lift Rating — Retracted 25,000 lbs.		
	Under Lift Rating — 100" Extension 12,000 lbs.		
	Wheel Lift Safety Straps		Shop Now
	Lift/Fork Adapters		Shop Now
	Aluminum Tow Angles		Shop Now
	Safety Tie-Down Chains		Shop Now
	Tow Bar 12,000 lbs. Rating		Shop Now

Class D.

	Minimum 50,000 lbs. GVWR Chassis
	30-Ton Recovery Equipment Rating

☐	250'L x 3/4" dia. Cable 6 x 19 Construction or OEM Specifications	Shop Steel	Shop Fiber
☐	Safety Chains 5/8" Alloy or OEM Specification	Shop Now	
☐	Two 12-Ton Snatch Blocks	Shop Now	
☐	Air Brakes w/Air Hookup Package		
☐	Air Hoses and Fittings	Shop Now	
☐	Steering Wheel Securement Device	Shop Now	
☐	Axle Covers/Caps	Shop Now	
☐	Tow Sling with 20,000 lbs. Rating		
☐	Tow Chains 5/8" Alloy or OEM Specifiactions	Shop Now	
☐	48"L x 4"W x 4"D & 60"L x 4"W x 4"D Wood Crossbeams		
☐	Pintle Hook	Shop Now	
☐	Hydraulic or Mechanical Winch(es)	Shop Now	
☐	Under Lift Rating — Retracted 32,000 lbs.		
☐	Under Lift Rating — 100" Extension 16,000 lbs.		
☐	Lift/Fork Adapters	Shop Now	
☐	Aluminum Tow Angles	Shop Now	
☐	Safety Tie-Down Chains	Shop Now	
☐	Tow Bar 20,000 lbs. Rating	Shop Now	