

CENTURY®

2465



The Century 2465 integrated towing & recovery unit has been designed to be an ideal match for the popular low-pro medium duty chassis. The 2465 is equipped with twin 12,000 lb. planetary winches and a recovery boom rated at 12 tons retracted and 5 tons extended. The Century 2465 is available in an 84" or 108" CA aluminum modular body that includes spacious tool compartments with a front tunnel box. The fabricated underlift is rated at 7,000 lbs. lift capacity at its fully extended reach using lifting forks. This makes it ideal for towing a wide variety of light- and medium-duty trucks, as well as automobiles.

Legendary Leadership

BOOM SPECIFICATIONS

Retracted	24,000 lbs.
Extended	10,000 lbs.
Maximum Angle	40°
Maximum Hook Height	147"
Maximum Reach Past Tailboard at Minimum Elevation	72"

UNDERLIFT SPECIFICATIONS

Fully Retracted (with Forks)	9,000 lbs.
Fully Extended (with Forks)	7,000 lbs.
Extended or Retracted with L-Arms	6,000 lbs.
Underlift Reach to Center of Fork Holder on the Ground	
Retracted	42"
Extended	76"
Positive Tilt	28°
Negative Tilt	12°
Tow Rating	20,000 lbs.

WINCH RATING & CABLE

Rating (first layer of drum) each Winch	12,000 lbs.
Diameter and Length (each winch)	7/16" x 150' IWRC

STANDARD FEATURES

- 60" Aluminum Modular Body with 1 Compartment Per Side
- 24" or 48" Aluminum Tunnel Box
- Dual Control Stations
- Planetary Winches
- Winch Cable Tensioners
- Winch Free Spool Handles
- 1 Set of 3" Lift Forks
- 1 Set of Fork Receivers
- Safety Chains, 5/16 Grade 70
- Safety Chain Storage Pockets
- Dual Hydraulic Pump with Split System
- Hydraulic Rear Jacks with Flipper Feet
- 6,000 lb. L-Arms with Pivoting Receivers
- L-Arm Storage Pockets
- Low Pull "D" Rings
- Federal Standard 108 Lighting
- Mud Flaps



The 2465 comes standard with a low-profile crossbar with removable ends, one set of lift forks, fork holders and a 6,000-lb. pivoting L-Arm System.



OPTIONAL FEATURES

- PTO
- Lanyard Remote Controls
- Additional Lifting Attachments
- 4,000 lb. Aluminum L-Arms
- Switch Panel
- Aluminum Dress-Up Kit
- Additional Work Lights
- Light Pylon
- Wide Load Light Bar
- Air & Electrical Hookups
- Combo 5th Wheel/Pintle Hook
- Trailer Ball Adapter



The fabricated underlift is rated at 7,000 lbs. lift capacity at its fully extended reach using lifting forks and has a tow capacity of 20,000 lbs. This makes the Century 2465 ideal for towing a wide variety of light- and medium-duty trucks, as well as automobiles.

CHASSIS RECOMMENDATIONS

GVWR	21,000 - 31,000 lbs.
Cab to Axle (Clear)84" or 108"
Maximum Frame Height	37"
Maximum Tire Size	255/70 R 22.5

All ratings are based on structural factors only, not vehicle capacities or capabilities. Specifications shown are approximations and may vary depending on chassis selected. Miller Industries Towing Equipment Inc. reserves the right to change or modify product and/or specifications without notice or obligation. Some equipment shown is optional.



Zips.com | 800-222-6047