




MODEL 345 PINTLE HITCH TRAILER



Proven Solutions for Your Hauling Needs!
1-800-428-5655 | www.landoll.com/trailers





Standard & Optional Equipment / Features

Model 345 Pintle Hitch Trailer



S=Standard O=Optional

MODEL 345	25 TON	50,000 lbs.
MAIN FRAME		
- Fabricated 80,000 PSI Yield Four Beam Design		S
- Fabricated Inner Beams 80,000 PSI Web and Top Flange, 100,000 PSI Bottom Flange		S
HITCH		
- Pintle Hook with 15,000 lb. Vertical Load Eye with Adjustment of 23"-32"		S
- 4' Hitch for Tractor without Bed Overhang		S
- 5' Hitch for Tractor with 1' Bed Overhang		S
- 7' Hitch for Tractor with 3' Bed Overhang		O
CROSSMEMBERS		
- 3" & 4" Jr. I-Beams Alternating on 8" Centers		S
WINCH		
- None		S
- 12,000 lb. Braden - Front Mount		O
- 20,000 lb. Braden - Front Mount		O
- Cable Roller Guide for Winch		O
- Wireless Remote Control		O
DECK AND FEATURES		
- 102" Wide		S
- 1 3/8" Apitong		S
- Deck Rating 40,000 lb. in 10'		S
- 9° Load Angle		S
ACCESSORIES		
- Approach Plate with (6) Keyhole Tie Downs		S
- Dual Hydraulic Controls Street and Curb Side		O
TIE DOWNS / CHAIN GOTCHAS		
- Double Keyhole Chain Slots and Stake Pockets on 24" Centers		S

MODEL 345	25 TON	50,000 lbs.
TOOL BOX		
- Curb and Street Side Mounted with Lockable Doors		S
- 14" H x 24" W x 24" D		
PARKING STANDS		
- Pin Drop		S
SUSPENSION / AXLES		
- SAF-Holland / Neway Air Ride RLU228, 22,500 lb. Capacity		S
- Centralized Grease System		S
- (2) 25,000 lb. Dual Tires, Oil Bath Bearings		S
BRAKES		
- 12.25x7.5 Full Air / Spring Brakes ABS, 4S2M		S
TIRES / RIMS		
- 235/75R 17.5 Double Coin Radial Tires		S
- 17.5x6.75 Tubeless Rims		S
- Hub Pilot / Steel Outboard Brake Drum		S
HYDRAULIC HOOK UP		
- Hydraulic Quick Couplers 2500 PSI - 20 GPM at Controls, 50 GPM Max		S
LIGHTS		
- Grote Clear Lens LED with Chrome Bezel (10-Year Warranty)		S
- Grote "Xtreme" Wiring Harness (7-Year Warranty)		S
FINISH / COLOR		
- Steel Grit Shot Blast to Bright Metal		S
- Zinc Rich Primer		S
- TGIC Polyester Powder Coat White, Black, Yellow, Blue, Red, Green, Sapphire Blue, Dark Gray		S
WEIGHT		
- 13,500 lbs. +/-3%		S

Pictures and content may include optional equipment and/or standard features that may not be standard on all models. Specification and design subject to change without notice. Weights and measurements are best estimates and should not be treated as actual. There are other features and optional equipment available. If you have any questions, consult the factory. Capacity ratings are frame capacities only. Actual load capacities may be restricted by factors such as gross axle weight ratings (GAWR) or state and federal regulations.



Call 1-800-428-5655


Proven Solutions for Your Hauling Needs!

www.landoll.com/trailers

1900 North Street | Marysville, KS 66508 | Ph: 785-562-5381 | Fax: 888-293-6779


Remember: Quality is Always a Bargain!

Scan for More!





GALVANIZING ***OPTION***
GALVANIZING
AVAILABLE ON ALL TRAILERS




Proven Solutions for Your Hauling Needs!
1-800-428-5655 | www.landoll.com/trailers





Galvanizing Option for Corrosion Resistance



Pictures and content may include optional equipment and/or standard features that may not be standard on all models. Specification and design subject to change without notice. Weights and measurements are best estimates and should not be treated as actual. There are other features and optional equipment available. If you have any questions, consult the factory. Capacity ratings are frame capacities only. Actual load capacities may be restricted by factors such as gross axle weight ratings (GAWR) or state and federal regulations.

Call 1-800-428-5655

Proven Solutions for Your Hauling Needs!

www.landoll.com/trailers

1900 North Street | Marysville, KS 66508 | Ph: 785-562-5381 | Fax: 888-293-6779

Remember: Quality is Always a Bargain!

