



MODEL 835 E / 835 E -HD / 845 E -HD AG DETACHABLE GOOSENECK



- 1½" Clearance with Teeth Seated in Fifth Tooth (4 Left, which will be needed with Front Flip Extension and One Axle Jeep Configuration)



- 16¼" Clearance with Teeth Seated in Highest Setting



- 21½" Clearance, Cylinders Fully Extended (Temporary Clearance at Slow Speed)



- Easily Adjustable Ground Clearance in 2" Increments
- Transport at any Height with Neck Teeth Seated



- RUST FREE Aluminum Pullouts to 13' Width (7,000 lb. Capacity Each on 835) (9,000 lb. Capacity Each on 835-HD) (14,000 lb. Capacity Each on 845)
- Pullouts are Strong as Steel yet Save 1,000 lb. of Weight
- Pullouts Adjustable on 6" Increments
- Heavy-Duty Steel Front Pullout Easily Adjusted by the Drivers



- Low Profile Front Approach
- Four Wheel or Tricycle Units can be Easily Loaded
- No Heavy Ramps
- Safe Loading Directly on Lower Deck
- Increased Driver Confidence while Loading

Proven Solutions for Your Hauling Needs!
1-800-428-5655 | www.landoll.com/trailers





Standard & Optional Equipment / Features

Model 835E / 835E-HD / 845E-HD Ag Detachable Gooseneck Trailer



S=Standard O=Optional

MODEL 835E	35 TON	70,000 lbs.
MODEL 845E-HD	45 TON	90,000 lbs.
MODEL 835E-HD	35 TON	70,000 lbs.
MAIN FRAME		
- Fabricated 100,000 PSI Four Beam Frame	S	S S
- Capacity - 70,000 lb. Distributed / 60,000 lb. Concentrated in 12'	S	S
- Capacity - 90,000 lb. Distributed / 90,000 lb. Concentrated in 16'		S
KINGPIN SETTING		
- 15" Pin Setting - 84" Swing Clearance 12' G/N	S	S S
- 15" Pin Setting - 72" Swing Clearance 10'7"	O	
CROSSMEMBERS		
- 5" x 3" High Tensile Strength Tubing on 18" Centers		S
- 6" x 3" High Tensile Strength Tubing on 18" Centers	S	
- 8" x 3" High Tensile Strength Tubing on 18" Centers		S
GOOSENECK, DECK AND ACCESSORIES		
- 11' 9" Gooseneck		S
- 10'7" Gooseneck		O
- 12' Gooseneck with Front Flip Provisions	S	S O
- 102" Removable Aluminum Front and Rear Decks	O	O O
- 102" Width	S	S S
- 120" Width (Some 835 and 845 Models)	O	O O
- 18 1/4" Deck Height (Loaded)	S	S S
- 19 1/4" Deck Height (Loaded)		S
- 1 1/2" Nominal, Apitong Full Width	S	S S
- 27" Aluminum Telescoping Side Extensions (Lower Deck)	S	S S
- Flag and Banner Package (6 Flags & 2 Overwidth Banners)	O	O O
TIE DOWNS / CHAIN GOTCHAS		
- Double Key Hole Chain Slots Located on 36" Centers	O	O O
- (2) D-Rings at Base of Rear Trunnion Flush Mounted on Top of Inner Beams	S	S S
- (4) D-Rings - Gooseneck Beam (Bolt On)	O	O O
- (4) D-Rings - Trunnion Main Beam (Bolt On)	O	O O
- Side Mounted D-Rings on 36" Centers	S	S S
- (2) D-Rings Web-Mounted Top of Trunnion	S	S S
- (2) D-Rings Rear of Trunnion, Flush Mounted on Top of Inner Beams	S	S S
- (2) D-Rings Back of Gooseneck	S	S S
- (2) D-Rings at Top of Trunnion Slope (Outer Web)	S	S S
TOOL BOX		
- 24"H x 14"W x 22.5"D Curb Side	O	O O
WINCHES AND ACCESSORIES		
- Worm Gear 12,000 lb. with 85' of 1/2" Cable		O
- Worm Gear 20,000 lb. with 85' of 5/8" Cable		O
- Planetary Gear 20,000 lb. with 85' of 5/8" Cable	O	O O
- Planetary 30,000 lb. with 85' of 5/8" Cable	O	O O

MODEL 835E	35 TON	70,000 lbs.
MODEL 845E-HD	45 TON	90,000 lbs.
MODEL 835E-HD	35 TON	70,000 lbs.
LIFT CYLINDERS		
- Horizontally Mounted		S S S
AXLES		
- (2) 25,000 lb. Dual Tire, Oil Bath Bearings	S	S S
SUSPENSION		
- SAF-Holland/Neway Air Ride, 25,000 lb. Capacity	S	S S
- Centralized Grease System	S	S S
- Air Raise and Lower Valve	O	O O
- Digital Air Weigh Scale System	O	O O
BRAKES / HUBS		
- Automatic Slack Adjusters	S	S S
- 16.5 x 7 Full Air / Spring Brakes, ABS, 4S2M	S	S S
- 22.5 x 8.25 Hub Pilot / Steel Outboard Hubs	S	S S
TIRES		
- 255/70R 22.5 LRH Double Coin	S	S S
- Spare Tire and Hub Pilot Type Rim (255/70R 22.5)	O	O O
WHEEL ACCESSORIES		
- Aluminum Wheel	O	O O
- Hubometer	O	O O
HYDRAULIC POWER SOURCE		
- Air Shift PTO and Wet Kit for Tractor - Not Installed	O	O O
- Hydraulic Quick Couplers 2,500 PSI - 20 GPM at Controls, 50 GPM Max	S	S S
- 11 HP Honda Engine Package with Front Cover Front Extension Mount	O	O O
- 25 HP Kohler Engine Package	O	O O
LIGHTS		
- Grote Clear Lens LED with Chrome Bezel (10-Year Warranty)	S	S S
- Grote "Xtreme" Wiring Harness (7-Year Warranty)	S	S S
FINISH / COLOR		
- Steel Grit Shot Blast to Bright Metal	S	S S
- TGIC Polyester Powder Coat	S	S S
White, Black, Yellow, Blue, Red, Green, Dark Gray, Sapphire Blue		
WEIGHT (BASE)		
- 48', 51' - 835AG - 18,000 lb., 18,900 lb. +/- 3%	S	S
- R-53' - 835AG - 20,700 lb. +/- 3%	S	S
- S120-53' - 835AG - 18,300 lb. +/- 3%	S	S
- S60-53' - 835AG - 19,300 lb. +/- 3%	S	S
- 53' - 845AG - 22,600 lb. +/- 3%		S
ESTIMATED WEIGHTS		

Pictures and content may include optional equipment and/or standard features that may not be standard on all models. Specification and design subject to change without notice. Weights and measurements are best estimates and should not be treated as actual. There are other features and optional equipment available. If you have any questions, consult the factory. Capacity ratings are frame capacities only. Actual load capacities may be restricted by factors such as gross axle weight ratings (GAWR) or state and federal regulations.

Call 1-800-428-5655

Proven Solutions for Your Hauling Needs!




www.landoll.com/trailers

1900 North Street | Marysville, KS 66508 | Ph: 785-562-5381 | Fax: 888-293-6779


Remember: Quality is Always a Bargain!

Scan for More!





GALVANIZING ***OPTION***
GALVANIZING
AVAILABLE ON ALL TRAILERS



Proven Solutions for Your Hauling Needs!
1-800-428-5655 | www.landoll.com/trailers





Galvanizing Option for Corrosion Resistance



Pictures and content may include optional equipment and/or standard features that may not be standard on all models. Specification and design subject to change without notice. Weights and measurements are best estimates and should not be treated as actual. There are other features and optional equipment available. If you have any questions, consult the factory. Capacity ratings are frame capacities only. Actual load capacities may be restricted by factors such as gross axle weight ratings (GAWR) or state and federal regulations.

Call 1-800-428-5655

Proven Solutions for Your Hauling Needs!

www.landoll.com/trailers

1900 North Street | Marysville, KS 66508 | Ph: 785-562-5381 | Fax: 888-293-6779

Remember: Quality is Always a Bargain!

