

6300

LOADOLL II

LOADOLL



Storio 40



Dual Hydraulic Controls Well protected, illuminated hydraulic controls are located just rear of the axle.

Proven Solutions for Your Hauling Needs! 1-800-428-5655 | www.landoll.com/trailers





Loadoll II



S=Standard O=Optional

MODEL LOADOLL II	
MAIN FRAME - 11,200 lb. Distributed Over Full Length of Deck - Rigid Tubular Steel Sub-Frame (Powder Coated Black), Full Length High Quality Nylatron Wear Pad (Deck Mounted) - Positive Bed Hold-Down-Frame Mounted with Safety Anti-Lock Tilt Lockout	S S S
CROSSMEMBERS - 3" Jr. I-Beam on 8" Centers	s
HYDRAULICS - PTO Pump, Oil Reservoir - Direct Mounted Pump with Cable Shift PTO and Warning Light - Special Hot Shift PTO / Pump for Auto Transmission	s s o
DECK AND FEATURES - Adjustable Stabilizer Legs - Dual Hydraulic Control Work Stations - Toe Board ¾" x 2-1/2" Tall - 1/8" Tread Steel Deck with Tread Side Down - 1/8" Tread Steel Deck with Tread Side Up - Skid Plate for Containers	S S O S O S
LIGHTS - FMVSS Grote LED Light Group with E-Chain Protection System - Backup Alarm	s o
GEARBOX - 15,000 lb. Capacity with ½" Chain	s

MODEL LOADOLL II	
HITCH - None	S
TIE DOWNS - Keyholes on Side (11 per Side on 25 ½' Bed) - (4) Keyholes in Rear Approach Plate	S S
TOOL BOX - 30" Steel Tool Box 18" x 18" with Stainless Door - 48" Steel Tool Box 18" x 18" with Stainless Door - 30" Steel Box 18" x 18" with Steel Door - 48" Steel Box 18" x 18" with Steel Door	0000
ACCESSORIES - Steel Bulkhead, Bed Mounted - Rear Work Lights Bulkhead Mounted - Rear Work Lights Bumper Mounted - Work Lights at Gear Box	s 0 0
FINISH / COLOR - Deck and Sub-Frame Powder Coat Black	s
Pictures and content may include optional equipment and/or standard features that may not be st	andar

Pictures and content may include optional equipment and/or standard features that may not be standard on all models. Specification and design subject to change without notice. Weights and measurements are best estimates and should not be treated as actual. There are other features and optional equipment available. If you have any questions, consult the factory. Capacity ratings are frame capacities only. Actual load capacities may be restricted by factors such as gross axle weight ratings (GAWR) or state and federal regulations.



Hydraulic System The Loadoll II uses welded hydraulic cylinders with chrome plated rods for long trouble-free service.









Proven Solutions for Your Hauling Needs! 1-800-428-5655 | www.landoll.com/trailers





Galvanizing Option for Corrosion Resistance





















