



4-Car Carrier



Some optional equipment shown.

- 20,000 lb. Aluminum Main Deck
- Available in 28' to 30' Lengths
- Maximize Your Payload per Mile
- Optional Wireless Remote
- Extended Cab-Carrier Option



Zips.com | 800-222-6047

Standard Features

- 102" Wide Aluminum Body
- High tensile double box 4 inch extruded floor system
- Heavy duty extruded sill w/ integral full length wear strips (top & bottom)
- Extruded double-box sides
- Full Length Subframe
- 12 Chain Locks
- Fully Hydraulic Wheel Lift
- Drop-In L-arms
- Bed Anti-tilt Lockout
- Inboard Tilt Cylinders
- 4 Light Tail Light Housing
- Illuminated Dual Controls
- 8 Side Body Marker Lights (4 per side)
- Mudflaps & Backup Alarm
- Federal Standard LED 108 Lighting
- Tow Light Plug
- Lubrication Fittings on All Pivot Points
- (2) 8,000 lb. Worm Gear Deck Winches with Tensioners
- 8,000 lb. Planetary Winch for Cab Carrier
- Air Free Spool on All Winches (Drivers Side)
- 4 Safety Chains

Carrier Length	Usable Cab-To-Axle (w/ cab carrier)	Min Frame RBM (each rail)
28'	202	1,800,000 in * lbs
29'	210	2,100,000 in * lbs
30'	218	2,100,000 in * lbs

4-car carriers should be mounted on chassis with low profile cabs and a minimum FAWR 12,000 lbs. for the cab carrier.



Specifications

- Body Width 97 I.D. x 102 O.D.
- Body Extension 120"
- Body Rating* 20,000 lbs. evenly distributed
- Wheel Lift Rating* 4,000 lbs. extended
- Cab Carrier Rating* 5,000 lbs. evenly distributed

Chassis Recommendations

- Recommended GVWR 33,000 lbs
- Accessible PTO opening
- Maximum Frame Height 42"
- Minimum Frame Height 36"

All ratings are based on structural factors only, not vehicle capacities or capabilities. Specifications shown are approximations and may vary depending on chassis selected. Miller Industries Towing Equipment Inc. reserves the right to change or modify product and or specifications without notice or obligation. Some equipment shown is optional.

Optional Features

- Additional Chain Locks
- 24 GPM Direct Mount Pump
- PTO
- Retractable Ladder
- Various Toolbox Options
- Factory Installation
- Pivoting L-arms
- AutoGrip™ II Wheel Lift
- Galvanized Subframe
- Wireless Remote Control
- Passenger Side Air Free Spool

Accessories

- Work Lights
- Switch Panel
- Magnetic Tow Lights
- J-Hook Chains
- Front Hookup Chains
- Trailer Ball Plate
- Pintle Hook Attachment

Note: Some option selections may not be compatible in all configurations.



Miller Industries Towing Equipment, Inc. reserves the right to improve or upgrade products without obligation. Ratings based on structural factors only, not vehicle capacities/capabilities. Specifications shown are approximations & may vary depending on chassis. Some equipment shown is optional.



Zips.com | 800-222-6047