

# Vulcan®

## 812 Intruder II



*PolyBody Body and Optional Equipment Shown*

- *Increased Rear Visibility*
- *Improved Hose Tracking System*
- *4 Available Body Options*
- *New Low Profile Crossbar & Jaws*
- *Enclosed Jaw Cylinders*



**Zips.com** | 800-222-6047



## Standard Features

- 60" C.A. Steel Modular Body
- Adjustable Body Width, 88" or 94"
- Auto Load Wheel Lift System
- Adjustable limiter switches on elevation & tilt functions
- 180° Pivoting Crossbar
- Self Centering Crossbar
- Tailboard Safety Chain Pockets
- Safety Chains
- Safety Chain Pocket Guards
- Wheel Lift Ratchets & Straps
- Driver & Passenger Side Tool Compartments
- In Cab Wheel Lift & Winch Controls
- 8,000 lb. Planetary Winch with 100' of 3/8" Cable
- Junction Box and Wiring Harness
- Mud Flaps
- Federal Standard 108 Lighting
- Tire Spacers (Flat Tires)

## Optional Features

- Clutch Pump or Pump/PTO
- Aluminum, Composite, or PolyBody Modular Body
- Steel Light Pylon
- Aluminum Tubular Light Pylon
- 24" Tunnel Tool Box (Steel, Aluminum or Composite)
- Motorcycle Attachment
- 5th Wheel Attachment
- Bolt on Tailboard "D" Rings
- Dress Up Packages
- Emergency Lighting
- Dollies
- Trailer Hitch Attachment

## Specifications

### BOOM

Recovery Boom (at boom end swivel).....	8,000 lbs.
Maximum Lift Angle.....	21°
Winch (Planetary).....	8,000 lbs.
Cable.....	3/8" x 100'

### UNDERLIFT

Lift Capacity Extended.....	4,000 lbs.
Tow Rating.....	7,500 lbs.
Maximum Reach.....	73"
Power Tilt.....	30° Arc

### CHASSIS RECOMMENDATION

Minimum C.A. (Cab to Axle).....	60"
Maximum C.A. (With Tunnel Tool Box).....	84"
Suggested GVWR.....	14,500 lbs.

All ratings are based on structural factors only, not vehicle capacities or capabilities. Specifications shown are approximations and may vary depending on chassis selected. Miller Industries Towing Equipment Inc. reserves the right to change or modify product and or specifications without notice or obligation. Some equipment shown is optional.



# Vulcan®



[Zips.com](http://Zips.com) | 800-222-6047