

XL BLADEMATE



- · 53-foot trailer opens to 184 feet with bumper
- · Steel treadplate fenders available on the front and rear
- Add 24" long bunks to provide additional loading areas across the main beams: rolling and adjustable non-rolling versions available
- · Rear-facing worklight at front, rated at 1200 lumens
- Red/green indicator lights on the toolbox front and rear signal if the power unit is on or off
- Air and electrical lines are well-protected inside turn table plates to keep them clean



trai the from

SELF-STEERING SYSTEM


The axles automatically rotate to keep the trailer behind the truck at all times; the kingpin rotates and prompts the axles to track with it. An override remote allows drivers to take full control as needed. A beacon light alerts the driver and pilot car when the axles are turning (past 3 degrees).

CONVENIENT EXTENSION

XL's trusted extendable technology is the key to hassle-free extension; all trailer beams as well as the pullout bumper are on greasable rollers. Experience the smooth, quick, convenient extension of an XL with the Blade Mate. Extend from 53 feet to 184 feet with the pullout bumper. The XL BM is even prepped for deck inserts which allow you to reach over 200 feet in length overall.







CAPACITY

capacity: 90,000 lb overall weight: 33,350 without bunks 35,140 lb with 2 bunks

OVERALL LENGTH & WIDTH

overall length: 53' closed, opens to 184' 2" with pullout bumper overall width: 102"

GOOSENECK

9' long 19" king pin setting 77" swing clearance 49" 5th wheel height 2 speed landing gear with handle on curbside bolt-on aluminum front fenders 2 d-rings on front 2 d-rings per side - 4 total 4 d-rings on rear of platform 20" loading platform on front 57" deck height on platform 1 pair of flag holders

MAIN DECK

T-1 flange, 80K web 13HP hydraulic power unit 51" loaded deck height 20" steel platform at rear with 4 d-rings and 6 chain slots telescoping main frame, 4 total sections with stops on 18" centers after total extension of 124" 2 pairs of flag holders 20' pullout, non-load bearing bumper with stops on 24" centers 1 pair d-rings in tail channel

MAIN DECK OPTIONS

24" long rolling bunk 24" long adjustable non-rolling bunk deck inserts

SUSPENSION

25,000 lb air ride raise and lower valve manual ride height control

SUSPENSION OPTIONS

liquid filled air gauge Air-weigh digital scale

AXLES

(3) 25,000 lb nominal 71" spacing hub pilot, outboard drums 2SIM ABS 12 1/4" x 7 1/2" brakes 1 pair spring brakes Tritronic hydraulic control kingpin steering system with wireless remote for over steering

AXLE OPTIONS

hubometer TP axles (same inner & outer bearings) dust shields cat eye systems disc brakes

WHEELS & TIRES

6.75 x 17.5 steel rims 245/70R/17.5 tires

WHEEL & TIRE OPTIONS

customer specified tires customer specified mud flaps aluminum mill wheels aluminum polished wheels Michelin tires PSI tire inflation system

LIGHTING

12V sealed Grote harness rubber mounted LED lights 3 tail light package with aluminum cover amber strope as 3rd stop turn tail rear facing work light on upper power on/off indicator system alignment indicator

PAINT

black, IH red, CAT yellow, white air & electric done after paint

PAINT OPTIONS

non-standard paint colors non-standard metallic paint

WARRANTY

1 year structural 1 year paint

AVAILABLE MODELS

XL90BM