

# **XL HDG: MINI DECK**



- 12-inch loaded deck height for tall loads
- · Low-profile design offers clearance
- · 5 ride height positions for deck height options
- · 13HP power unit in the base of the gooseneck
- · 11-foot long hydraulic neck for fast loading
- Full-width platform adds loading space
- · 12 d-rings provide tie-down locations





# **RUGGED & VERSATILE MAIN DECK**

XL HDG Mini-decks feature a 12-inch loaded deck height with 4 inches of ground clearance. XL Mini-decks are available in capacities from 60,000 pounds to 80,000 pounds. They come in both 48-foot long and 53-foot long with either 28 feet or 33 feet in the well, respectively.

# UNIQUE THREE BEAM DESIGN

XL's superior three beam design uses 4-inch junior I-beams on 18"-inch enters, resulting in a lighter yet exceptionally strong trailer. With empty base weights as low as 19,650 pounds, drivers can easily scale out to maximum payload. This design uses steel flooring in the center deck and Apitong in the outer bays.





# XL 60 HDG: MINI CAPACITY

capacity: 60.000 lb overall concentrated: 60,000 lb in 16'

#### XL 70 HDG: MINI CAPACITY

capacity: 70,000 lb overall concentrated: 70,000 lb in 16'

#### XL 80 HDG: MINI CAPACITY

capacity: 80,000 lb overall concentrated: 80,000 lb in 16'

#### **OVERALL LENGTH & WIDTH**

overall length: 48' or 53' overall width: 102"

#### GOOSENECK

hydraulic low-profile full-width 49" 5th wheel height 86" swing clearance 16" king pin setting (2) bent d-rings per side 1 1/8" Apitong decking - flush 13HP power unit with steel cover

frame reinforcement for flip neck

# **GOOSENECK OPTIONS**

pan style d-rings 36" flip neck extension

### MAIN DECK

48' version: 28' long 53' version: 33' long T-1 flange, 80K web (2) 8" fabricated i-beams center box beam 12" loaded deck height 4" ground clearance 4" jr i-beam cross members on 18" centers 80 only: mid-header 12 bent d-rings per side 11/8" Apitong decking - flush in outer bays steel floor in center deck ramp tapers to 4"

#### MAIN DECK OPTIONS

13/8" Apitong decking - raised additional clearance lights 4-way plug(s) chain drops additional d-rings Durabek non-slip on center deck

#### REAR BRIDGE

40" deck height 1 1/8" Apitong decking flush 2 flag holders 2 bent d-rings in tail channel 2 pair pan-style d-rings, on corners frame reinforcement for flip axle

#### **REAR BRIDGE OPTIONS**

clearance lights pull out lights 4" amber strobe tail light additional tail light battery back up (1) 4-way plug 1 3/8" Apitong decking - raised dock bumpers

# SUSPENSION

25,000 lb air ride raise and lower valve manual ride height control

#### SUSPENSION OPTIONS

liquid filled air gauge Air-weigh digital scale control in aluminum box - ball valves electric dump valve with 4-way plug and wire

# AXLES

(2) 25,000 lb nominal hub pilot, outboard drums 4S2M ABS 16 1/2" x 7" brakes (2) pair spring brakes

#### **AXLE OPTIONS**

PSI tire inflation system hubometer TP axles (same inner & outer bearings)

#### WHEELS & TIRES

8.25 x 22.5 steel rims 255 / 70R / 22.5 tires

#### WHEEL & TIRE OPTIONS

aluminum mill wheels (inside) aluminum mill wheels (outside) aluminum polished wheels (outside) aluminum Durabright wheels (outside) Michelin 255/70R/22.5 tires

#### LIGHTING

12V sealed Grote harness rubber mounted LED lights 2 tail light package with aluminum cover 2 clearance lights per side 1 mid-turn light per side 7 pole electric socket

# PAINT

black, IH red, CAT yellow air & electric done after paint

#### PAINT OPTIONS

non-standard paint colors non-standard metallic paint

#### WARRANTY

5 year structural 1 year paint

### **AVAILABLE MODELS**

XL 60 HDG: Mini-deck XL 70 HDG: Mini-deck XL 80 HDG: Mini-deck