

XL MECHANICAL FULL-WIDTH GOOSENECK



- Rear bridge features a 45° transition and traction aids
- 18" loaded deck height with 6" ground clearance
- · Manual ride height control and double donuts
- · Lockable toolbox with chain rack and light
- · Rear coupler uses an angled control panel
- · Front ramp tapers to 4 inches
- · Rear is reinforced for flip axle



h

VERSATILE HAULING CAPABILITY

Manual ride height control and double donuts allow the main deck height to vary 1.5 inches in the wheel area and 1.5 inches at the neck to suit drivers' needs over varying terrains.

Add a flip axle when your load requires it. Add a 36" flip neck extension to the XL 90 MFG to get over a four axle truck.

FULL EQUIPPED MAIN DECK

The XL MFG deck is fully equipped for versatile hauling, with fourteen half-inch chain drops per side, eight bent d-rings per side, and removable swingout outrigger brackets on 24-inch centers. The rugged Apitong decking stands up to years of wear and tear.





XL 80 MFG CAPACITY

capacity: 80,000 lb overall concentrated: 70,000 lb in 16'

XL 90 MFG CAPACITY

capacity: 90,000 lb overall concentrated: 80,000 lb in 16'

OVERALL LENGTH & WIDTH

overall length: 48' overall width: 102"

GOOSENECK

mechanical detachable full-width 10' long 49" 5th wheel height 84" swing clearance 16" king pin setting with 3/8" plate 2 bent d-rings per side 2 pan style d-rings per side, on corners

1 1/8" Apitong decking flush aluminum mudflaps double donut front connector plate toolbox in base w/ lockable aluminum lid, chain rack, light XL 90 MFG only: brackets for flip neck

GOOSENECK OPTIONS

pull out lights 1 pair clearance lights 13/8" Apitong decking - raised registration holder triple donut front connector plate

MAIN DECK

29' long T-1,80K web (4) 12" fabricated i-beams 18" loaded deck height 6" ground clearance 6" & 4" jr. i-beam cross members on 12" alt. centers 8 bent d-rings per side 1 1/8" apitong decking flush, center covered ramp tapers to 4" (14) 1/2" chain drops per side removable swing out outrigger brackets on 24" centers

MAIN DECK OPTIONS

center deck open storage compartments in front of main deck removable swing out outriggers Oak outrigger planks, 2" x 10" 13/8" Apitong decking - raised clearance lights 4-way plug(s) XL 90 MFG only: 36" flip neck

REAR BRIDGE

9'long 40" deck height 1 1/8" apitong decking flush 2 flag holders 2 stake pockets in tail channel 2 pan style d-ring per side, on corners frame reinforcement for flip axle 66" wide bumper at rear

REAR BRIDGE OPTIONS

1 pair clearance lights pull out lights 4" amber strobe tail light additional tail light battery back up (1) 4-way plug 13/8" Apitong decking - raised dock bumpers

SUSPENSION

25,000 lb air ride raise and lower valve manual ride height control

SUSPENSION OPTIONS

liquid filled air gauge Air-weigh digital scale control in aluminum box - ball valves electric dump valve with 4-way plug and wire

AXLES

(2) 25,000 lb nominal 54" spacing hub pilot, outboard drums 4S2M ABS 16 1/2" x 7" brakes 2 pair spring brakes

AXLE OPTIONS

hubometer TP axles (same inner & outer bearings)

WHEELS & TIRES

8.25 x 22.5 steel rims 255 / 70R / 22.5 tires

WHEEL & TIRE OPTIONS

aluminum mill wheels (inside) aluminum mill wheels (outside) aluminum polished wheels (outside) aluminum Durabright wheels (outside) Michelin 255/70R/22.5 tires Goodyear 275/70R/22.5 tire (41" rear bridge)

LIGHTING

12V sealed Grote harness rubber mounted LED lights 2 tail light package with aluminum cover 6 clearance lights per side 1 mid-turn light per side

PAINT

black, IH red, CAT yellow air & electric done after paint

PAINT OPTIONS

non-standard paint colors non-standard metallic paint

WARRANTY

5 year structural 1 year paint

AVAILABLE MODELS

XL80 MFG XI 90 MFG

other custom capacities also available, ask your sales representative for details