

XL POWER TAIL



FEATURES

- · Foot hole and grab handle for access to upper deck
- 9' pop-up ramp from deck to neck
- · 18,000 lb winch with air kickout
- · 25,000 lb tail lifting capacity
- · Work light at rear of neck
- · 2 function wireless remote
- · Star traction or steel tread plate



UNIQUE HYDRAULIC TAIL DESIGN


The tail is comprised of two sections – an 8-foot 8-inch platform ramp and a 60-inch flip tail. Both hinge points stay clean thanks to lug style hinges. These hinges prevent debris from accumulating.

HANDLES HARD-TO-LOAD EQUIPMENT

With a load angle of 10 degrees, the hydraulic tail is equipped to easily handle hard-to-load equipment such as manlifts, rollers, forklifts and paving equipment. The tail features a lifting capacity of 25,000 pounds for loads centered on the main platform.







CAPACITY

capacity: 80,000 lb overall concentrated: 50,000 lb in 10'

OVERALL LENGTH & WIDTH

overall length: 48' or 53' overall width: 102"

GOOSENECK

9' long full-width
90° slope
16" king pin setting
86" swing clearance
49" 5th wheel height
steel tread plate decking
(2) d-rings per side
2 speed landing gear with handle
on driver side
wet line hydraulics to run off truck
hydraulic levers on driver side

planetary drive 18,000 lb hydraulic winch with 75' of 1/2" cable & air kick out

2 function wireless remote for winch

2 toolboxes with lids

9' long pop-up ramp, deck to neck integrated foot step and grab handle, on both sides

GOOSENECK OPTIONS

13HP honda power unit
no pop-up ramp
30,000 lb winch
20,000 lb winch
12,000 lb winch
work-around pulley for winch cable
bolt-on winch guard
8 function wireless remote
10 function wireless remote

MAIN DECK

T-1 flange, 80k web 48' OAL: 30' 4" long 53' OAL: 35' 4" long 36" loaded deck height 1 3/8" Apitong decking - raised 1/4" tread plate covered wheels
18" fabricated i-beams
10" & 8" jr. i-beam cross members on
alternating 12" centers
5 d-rings per side
stake pockets and chain slots
on alternating 24" centers, sides
chain slots down on 48" centers,
center deck
2 pairs of flag holders

MAIN DECK OPTIONS

double drop design additional d-rings

TAIL SECTION

13' 8" hydraulic tail: 8' 8" platform 60" fold under flip tail automatic flip tail lock traction aids star traction plate decking

TAIL SECTION OPTIONS

tread plate decking

WHEELS & TIRES

6.75 x 17.5 steel rims 245 / 70R / 17.5 tires

WHEEL & TIRE OPTIONS

255 tires changes rear deck height to 39" aluminum mill wheels aluminum polished wheels customer specified tires customer specified mud flaps Michelin tires PSI tire inflation system

SUSPENSION

25,000 lb air ride

SUSPENSION OPTIONS

liquid filled air gauge Air-weigh digital scale

AXLES

(2) 25,000 lb nominal 49" axle spacing hub pilot, outboard drums 4S2M ABS spring brakes on 2 axles 12 1/4" x 7 1/2" brakes auto slack adjusters air dump on both axles

AXLE OPTIONS

hubometer TP axles (same inner & outer bearings) dust shields cat eye systems disc brakes

LIGHTING

12V sealed grote harness rubber mounted led lights 3 tail light package 1 mid-turn signal per side 2 clearance light per side 7 pole electrical socket

LIGHTING OPTIONS

amber strobe as 3rd tail light extra clearance lights

PAINT

black, IH red, CAT yellow air & electric done after paint

PAINT OPTIONS

non-standard paint colors non-standard metallic paint

WARRANTY

5 year structural 1 year paint

AVAILABLE MODELS

XL 80 P