

# ZACKLIFT

## Inexpensive Solution

### Inexpensive to Buy Inexpensive to Operate

FIFTHWHEELER owners report paying for the equipment in 6 months. Make money transporting everything a half-a-million dollar tow truck can at a fraction of the cost.

"The investment I made in buying my Zacklift, paid for itself in the first six months."

Jim Jordon, Jordon Automotive

### Simple to Install

Delivered to your front door factory assembled, wired, plumbed and ready to get to work. Every possible step of the installation is factory completed. The FIFTHWHEELER arrives hookup ready, just like a semi-trailer.

## FIFTHWHEELER



"I looked around and kept hearing about the Zacklift FIFTHWHEELER. I called Zacklift and talked to Karl. He was really helpful. I couldn't find anything else on the market that compared to all the features in the Zacklift. You can buy the cheap bar-style lift but they're not damage-free and I sure didn't think they were safe. Now I tow everything a quarter million dollar tow truck can do. I can hook up to anything. We run about a six hundred mile radius from Joplin Missouri. We run through scales all the time and never have to worry about it. I should have bought this FIFTHWHEELER a long time ago."

Trick My Truck's Bryan Martin

## WATCH THE VIDEO

Scan the square, or go to:  
<http://www.youtube.com/watch?v=Cs3roEAOLrA>



**ZIP'S TRUCK**  
EQUIPMENT INC.

Call 800-222-6047

[www.zips.com](http://www.zips.com)





All hoses, wiring and air factory pre-engineered and internally routed through FIFTHWHEELER beam.

Your choice of electric over manual hydraulic PTO ready valve, or 12-volt self-contained system, plumbed and ready at the factory. 15' corded remote control included.

25% lighter than any other detachable underlift unit on the market. Light weight and forward positioning allows for hauling larger payloads without toping out the scales.

Safety chain attachment points.

Chain pockets for storage in beam.

7 pin plug for tow lights and vehicle in tow.

Plumbed for glad hands and airtools.

LED stop, signal and tail-lights complete with wires housed inside beam.

5 sets of forks with fork rack included.

Strut system safeguards against load shifting and provides greater stability under side load.

Engineered for the fastest disconnect in the industry.

No weld attachment points for 20k and 30k winches.

Hydraulic, pneumatic and electrical quick disconnects.

9' long, 44.5" distance from kingpin to forward end of beam.

Powder coated beam for durability and long life finish.

Adjustable kingpin.

Fits American truck frames 33" to 35" wide.

Clamps to frame.

Fits European frames 840mm to 890mm wide.

Slim design to go between frame rails and airbags.

Leveler stands for backing under, just like a semi-trailer.

High quality cardinal industrial finish.

3 way fork reciever for multiple positions and heights.

Exceptional low profile for more single picks under low bumpers.

"Million mile Roller Bearing" in critical pivot hub for extended life.

T1 steel fabricated by dedicated Zacklift welders, some with 30 years' experience and devotion to Zacklift products.

Hooks up and drops just like a semi-trailer in under 10 minutes.

All mounting hardware stays with the FIFTHWHEELER when removed with no additional steps.

Easily mounts on multiple trucks.



	<b>Z30</b>	<b>Z303</b>	<b>Z402</b>	<b>Z403</b>
Retracted Lift Rating	32,000 lbs	32,000 lbs	40,000 lbs	40,000 lbs
Extended Lift Rating	18,000 lbs	13,000 lbs	26,000 lbs	18,000 lbs
Tow Rating	85,000 lbs	85,000 lbs	100,000 lbs	100,000 lbs
A Retracted Distance	56"	60"	58"	67"
B Reach	100"	119"	103"	135"
C Reach w/12" Extensions	112"	131"	115"	147"
D Dist. from Tailboard when Stored	11"	11"	12"	12"
E Upward Tilt, Max Lifting Height	22 deg. 65"	22 deg. 71"	22 deg. 68"	22 deg. 80"
F Tilt Below Ground	8 deg. 13"	8 deg. 15"	8 deg. 14"	8 deg. 21"
G Lift Cylinder Down Stroke	17"	17"	17"	17"
Weight	2583 lbs	2756 lbs	3578 lbs	4109 lbs
Suggested Wheelbase	260" to 280"	260" to 290"	270" & Up	290" & Up







## Zacklift Gull Wing Tool Box

Zacklift's trademark aerodyne toolboxes measure 71"x16" high x28" at the base. Polished aluminum doors flip up for close highway access and look like a million bucks! Store all forks on the installed fork racks and an entire Deluxe Accessory Package. Valves or power source are factory installed and plumbed. Zacklift's toolboxes include factory installed mounting hardware and drive off completely like a semi-trailer.

## 20k & 30k Warn Planetary Winches

Factory installed on the Zacklift FIFTHWHEELER, the winch package includes the Z10-1019A Zacklift Cable Guide mounted on the Zacklift's main upright section. Also included is the necessary valve work section, factory installed in-series on the Electric/Hydraulic Zacklift Valve. No-weld attachment points are provided on every FIFTHWHEELER beam for adding winch later. The 30XL and 20XL winches are Warn's ultra-duty series, with 30,000 and 20,000 lbs. of pulling power. Both are hardened aircraft-grade nickel with air clutch and spring applied disc brakes, while being permanently lubricated. Winches feature a 2-stage planetary gear train for speed and reliability.

## In the Ditch's Pro Series 70

Zacklift teamed with In The Ditch Towing Products to provide a customized FIFTHWHEELER Toolbox. 70"x18"x18", 1/8" thick aluminum, the toolbox door has a 400lb. rating so it can be used as a step. Zacklift's Valve or Power System is factory installed inside, and hoses and fittings are routed through customized, rear, weather-proof cut-outs. Boxes drive off completely and stay with the FIFTHWHEELER. All of the In The Ditch toolbox accessories can be added.

See them and more details at:  
[http://www.intheditch.com/FW2\\_ITD1570.php](http://www.intheditch.com/FW2_ITD1570.php)



## BigFoot STIFFLEGS

Engineered for secure mounting to the FIFTHWHEELER beam, the legs operate independently of each other with two additional valve sections installed in the Zacklift Valve. Rated at 25,000 pounds of push per leg, the Stifflegs extend 24", a full 12" below-ground for deep travel. 5"x5"x 3/8" outer tubing, and 4"x4"x1/2" inner tubing, Zacklift's Stifflegs hold every load the 20K and 30K winches can throw at them. Engineered with the same unique 'Flip Feet' of Zacklift's 70,000 lb Stifflegs, the legs allow operator to pull one pin to flip between flat on-road stabilizing and the rugged off-road claw.

## Aluminum Fenders

Zacklift has customized these fenders with FIFTHWHEELER mounting hardware, allowing them to drive-on and off with the FIFTHWHEELER. The smooth aluminum is polished to a mirror-like finish to compliment the high-quality finish of the Zacklift. The fenders can mount independently or with the toolboxes. Fenders are 102" and can be trimmed to fit.

