



1-800-222-6047

making you the towing leader

2013 TrailMax FWTD-70-TA Sliding Axle Trailer, , NT12338

Specifications

On Order

- VIN# 5UCFT5025DA001631
- Capacity (Distributed): 70,000#
- Concentrated Load: 50,000# in 10'
- Trailer Weight: 17,580#
- Frame Construction: Fabricated 4-Beam Design A-656 High Tensile
- Crossmembers: 4" & 3" Tubular On 12" Centers
- Hitch: King Pin Type 150,000 PSI Ultimate Strength, 115,000 Yield
- King Pin Setting: 18"
- Swing Clearance: 81"
- Loaded Deck Height: 36"
- Deck Width: 102"
- Load Angle: 6 Degrees
- Dump Angle: 16 Degrees
- Landing Gear: 2 Speed 70,000#, 100,000# Static Load
- Load Securement: 2-Way Chain Slot/Stake Pocket Design
- Undercarriage: Hydraulically Actuated 192" Traveling Axle System
- Hydraulic System: 2500 PSI 15 GPM 3-Stack Valve Plumbed To Quick Disconnects
- Tool Compartment: 2 Each In Fifth Wheel Upper Deck
- Winch: 20,000# Hydraulic 2-Stage Planetary Gear w/Recessed Cable Rollers
- 2 Function Wireless
- Amber Strobe/Tail Light
- Axles: 2 Each 25,000# Capacity, 5" Round 1/2" Wall Thickness, 71 1/2" Track
- Hubs: Oil Bath Type w/Unimount Hub & Drum, 8 On 275mm Bolt Circle
- Brakes: 12 1/4" x 7 1/2" S-Cam Full Air Brakes w/Maxi Spring Brakes On Both Axles, Automatic Slack Adjusters, Equipped w/2S 1M Anti-Lock Braking System
- Drums: Steel Outboard Type
- Suspension: Ridewell Model 240 Air Ride
- Wheels: 17.5" x 6.75" Uni-Mount 8 On 275mm Bolt Circle, Aluminum Wheels w/Lug Nuts
- Tires: 215/75R17.5 Radial Load Range H
- Finish Preparation: 5 Stage Acid Pre-Treatment
- Base Coating: DuPont 2-Component Epoxy Primer Sealer
- Finish Coating: DuPont 2-Component Urethane Enamel Top Coat
- Electrical: Trucklite Modular System w/Rubber Isolated, Sealed Beam LED Lighting, Protected In Tube Construction
- Decking: 1 3/8" Apitong Hardwood
- Various Options: Spare Tire, Spare Tire Carrier, Apitong Decking, Traction Devices, D-Rings, Belt Winches, 48" Underbody Toolbox, Custom Paint & Detail

While all information contained in this literature and other advertising has been obtained from sources deemed reliable, neither Zip's Truck Equipment, Inc., or its owners or agents, shall be liable for the correctness of descriptions. This brochure, as in all printed matter regarding this sale, is merely a guide and subject to additions or deletions. All purchases are based entirely on the personal inspections and/or opinion of the buyer.