

Product Data Sheet

No. 27045 - 08/16

H.D. OPEN GEAR & WIRE ROPE LUBE

AEROSOL

PRODUCT NUMBERS:
7045 - 12 OZ. NET WT. AEROSOL

I. GENERAL DESCRIPTION

Description: A tough and pliable oxidized asphalt and petroleum oil lubricant with extra adhesion properties for demanding applications. Works at temperatures from 0° to 160°F (-18°F to 71°C)The dark color and foaming action ensures total uniform coverage. For industrial use in manufacturing facilities. Not for retail sale.

Benefits: This product reduces wear and noise, waterproofs, and penetrates deep into metal pores for complete lubrication. Protects against rust and corrosion in both indoor and outdoor environments. This lubricant withstands extreme temperatures and pressure. Will not become brittle or breakdown under prolonged use. Does not weather or wash away.

Applications: Use on all wire rope and open gears, fifth wheels on tractor trucks, screw threads, drive chains, die-set leader pins, and flexible couplings.

Directions: Shake can well before using for at least 30 seconds. Spray 12-14 inches from surface. Vary pressure for density. For best results, apply to bend of wire rope where strands are spread. Operates best at room temperature (70°F). To keep sprayhead from clogging, clear head by inverting can and spraying for two seconds after use. If clogging does occur, remove tip and soak in mild solvent. Do not use on electrical equipment or machinery while in operation.

Limitations: Please refer to the Safety Data Sheet for specific information on material hazards, etc. Not for use on bronze and copper due to sulfur content. Not recommended for anti-friction bearings.

Packaging:

Aerosol:	Cans (211x604)	12 net wt. (340 g)	14.4 fl. oz. (425 ml)
	Case (12/case):	14 lbs. (6.35 kg)	0.47 CF (0.013 CM)

II. CHARACTERISTICS & PROPERTIES

Specification:

None

Appearance:

Foamy thick sticky liquid

Color:

Black

Odor:

Hydrocarbon

Dry Schedule:

Not applicable

Performance and Chemical Properties:**Aerosol**

Weight per gallon	6.4 lbs.
Specific gravity	0.8
Viscosity in centipoise	N/A
Flammability: Label marking	Flammable
Flash point.....	<0°F (-18°C)
Active ingredients by weight.....	55%
Volatile Organic Compound level.....	44%
Operating temperature range.....	40° to 110°F (5° to 43°C)
Pour point.....	N/A
Dielectric strength.....	N/A
Lubricity (FALEX FLC Test).....	50 ft. lbs.
Penetrating ability.....	Excellent
Corrosion protection.....	Good
Food contact rating	N/A

Base Materials:.....Aliphatic Petroleum Distillates**Propellant System:**Hydrocarbon

III. SHIPPING, STORAGE AND HEALTH

Aerosol

UN number	UN1950
Proper Shipping Description	Aerosols
Hazard Class.....	2.1
Packing Group	N/A
Limited Quantity	Yes
Warehouse storage level number	NFPA 30B Level 1
Storage temperature	32° to 120°F (0° to 49°C)
Shelf life	1 to 5 years
HMIS ratings	
Health	2
Fire.....	4
Reactivity	0

IV. MISCELLANEOUS

Contains no Ozone Depleting Substances (O.D.S.)

V. WARRANTY

1-year warranty to the original registered owner on all products from date of purchase. User returns, exchanges and defective refunds must be made with the original place of purchase. Because Aervoe cannot control Buyer's handling or use of product, Aervoe makes no warranty expressed or implied when not used or stored in accordance with directions. Aervoe shall not be liable for cost of labor, incidental or consequential damages, and this warranty is limited to replacement or repair of product or credit of purchase.