



SALTDogg®

SPREADERS

3, 4, & 4.5 CU. YD. SALT & SAND SPREADERS

GAS ENGINE OR HYDRAULIC DRIVE



1400500SS
Shown with optional
LS1 and **LB8663SST**

| PART NO. | DESCRIPTION | WT. |
|-------------------------------------|--|------------|
| NEW 1400475SS | 3.0 cu. yd. 96" Stainless Steel Spreader Kit, Gas Engine | 1,470 lbs. |
| NEW 1400475SSH | 3.0 cu. yd. 96" Stainless Steel Spreader Kit, Hydraulic Drive | 1,405 lbs. |
| 1400500SS | 4.0 cu. yd. 108" Stainless Steel Spreader Kit, Gas Engine | 1,500 lbs. |
| 1400500SSH | 4.0 cu. yd. 108" Stainless Steel Spreader Kit, Hydraulic Drive | 1,435 lbs. |
| 1400550SS | 4.5 cu. yd. 120" Stainless Steel Spreader Kit, Gas Engine | 1,560 lbs. |
| 1400550SSH | 4.5 cu. yd. 120" Stainless Steel Spreader Kit, Hydraulic Drive | 1,500 lbs. |
| OPTIONS & ACCESSORIES: | | |
| LS1 | 12-Volt Liquid Spray System, Cab Control, Poly Reservoir, 55 gal. | 48 lbs. |
| *LB8663SST | Stainless Steel D.O.T. Spreader Lightbar, 9-Hole Round (8"x3"x66") | 28 lbs. |
| 3008560 | Hopper Spreader Tailgate Lock Kit | 40 lbs. |
| 1496505 | Nylon Ratchet Strap Mounting Kit (4 straps to a set) | 9 lbs. |
| <i>* Lights/wiring not included</i> | | |

IDEAL FOR HEAVY-DUTY MUNICIPAL & COMMERCIAL APPLICATIONS

Designed for dump bodies and flat beds with a GVW chassis of 15,000 to 26,000 lbs. and is available with either hydraulic motor drive or 10½ H.P. gas engine.

GENERAL:

- Self contained hopper
- Spreads free flowing materials sand and/or salt
- Spread width of 4' to 30'

MATERIAL HOPPER:

- 12 gauge 304 Stainless steel with continuously welded seams.
- All hopper sides are formed with a continuous "J" channel profile for added rigidity and strength. Six (6) 12 gauge body gussets.
- Optimum material feed is maintained by hopper side walls sloped at 45°
- Heavy duty, 4 section hinged top grate is standard. Bars are ¼" diameter located on 3" center grid (installed).
- Built-in four corner lift loops.

CONVEYOR:

- Conveyor is 12½" wide, all steel pintle chain type (#667H Pitch), with 1/4" x 1" crossbars on 4-5/8" centers.
- Replaceable 10 gauge stainless steel chain shields.
- Replaceable 10 gauge stainless steel conveyor floor.
- 10 gauge stainless steel inverted Vee
- Conveyor driven by 20:1 ratio worm gearbox utilizing tapered bearings
- Conveyor chain is adjustable for chain take up, providing optimum performance and drive life.
- Chain drive and idler sprockets are 6-tooth cast sprockets keyed to 1¼" shafts.
- Conveyor chain wiper minimizes waste.

SPINNER ASSEMBLY:

- Spinner chute has two adjustable internal baffles
- Four (4) external baffles (3 adjustable, 1 fixed)
- 18" x ¾" thick polyurethane spinner disc
- Hydraulic model's chute utilizes (4) spring loaded stainless steel quick detach pins for ease of: material unloading, tow hitch access, and storage.
- Bolt-on spinner housing minimizes replacement cost.

POWER SOURCE:

- Hydraulic Drive: Two Independent hydraulic motors (15 GPM @ 1,500 PSI)
- Gas Engine: 10.5 horsepower, Briggs & Stratton Intek


OPTIONAL EQUIPMENT:

- Nylon strap mounting kit
- Tailgate latch kit
- Liquid spray systems, electric
- Stainless Steel D.O.T. Spreader Lightbar


DIMENSIONS:

- 3 cu. yd. – Overall Length, 96"; Width, 70"; Height, 45"; Recommended use, dump bodies and flat beds with a GVW chassis of 15,000 to 26,000 lbs.
- 4 cu. yd. – Overall Length, 108"; Width, 70"; Height, 45"; Recommended use, dump bodies and flat beds with a GVW chassis of 15,000 to 26,000 lbs.
- 4½ cu. yd. – Overall Length, 120"; Width, 70"; Height, 45"; Recommended use, dump bodies and flat beds with a GVW chassis of 17,500 to 26,000 lbs.


Buyers Products Company reserves the right to change material, dimension and/or component specifications without notice.




Standard Heavy-Duty Hinged Top Screens



Optional Lightbar
(lights/wiring not included)



Optional Liquid Spray System
(55 Gallon)



Optional Tail Gate Latch Kit

CONTACT:

ZIP'S TRUCK EQUIPMENT INC.

800-222-6047

www.zipps.com

Your Authorized SaltDogg® Distributor

