



► Pulsator® 451 Plus | Strobe Beacon

FEATURES

- Low-profile, polycarbonate base strobe beacon
- Easily replaceable helical strobe tube
- Automatic adjustment to function at any voltage from 12-48VDC
- Three-year warranty

APPROVALS

- 8-joule: SAE J845 Class 2 (SAE J1318 Class 2, 2009)

The Pulsator® 451 Plus features a state-of-the-art, 8-joule, power supply for improved light output and warning effectiveness. This low-profile strobe combines advanced dome optics with a high-performance power supply to produce a brilliant flash that meets SAE Class 2 requirements.

Pulsator 451 Plus strobes are exceptionally durable. The power supply is moisture and vibration resistant and protected against reverse polarity, voltage spikes and RFI. The patented base design and O-ring gasket combine to seal out moisture and contaminants. All models feature modular construction that provides quick access to internal components. The impact-resistant, polycarbonate, dome and base provide added durability in heavy-duty applications.

Heavy Duty models feature a gel-filled base that completely encases the power supply for extra protection against vibration and moisture. The encased power supply allows superior performance in extreme high-vibration environments.

Pulsator 451 Plus models are available in 8-joule (double and quad-flash) and 12-48 VDC versions. All models use a helical strobe tube that is easily replaceable. All models include the necessary mounting hardware.



Heavy Duty Pulsator models use gel to protect complainants against vibration

Specify Model

- 8J, 10.7W, 12-48VDC, double flash
- 211680-02 Permanent mount, Amber; -03(Blue); -04(Red); -05(Clear); -06(Green)
- 211682-02 Magnetic mount, Amber; -03(Blue); -04(Red); -05(Clear); -06(Green)
- 211823-02 HEAVY DUTY, permanent mount, Amber; -03(Blue); -04(Red); -05(Clear); -06(Green)

Accessories and Kits

- 200069-95 Bottom plate
- 210890 Kit, magnetic mount
- 210893 1/2" pipe mount
- 210894 3/4" pipe mount
- 210895SSG 1" pipe mount

Specifications


Flash Rate	80/min. (Double)
Voltage	12-48 VDC
Amp Draw	0.9 @ 12V to 0.25 @ 48V (8-joule)
Joules	8J (Double/Quad)
Output Power	10.7W (Double)

Physical Specifications

Height	4.0 in (102 mm)
Diameter	6.5 in (165 mm)

Ship Weight

- 1.3 lbs (0.6 kg)
- 1.6 lbs (0.7 kg) (Heavy Duty)



210890



210895SSG



210893



210894



200069-95



Pulsator is a trademark of Federal Signal Corporation.

©2016 Federal Signal Corporation. M7112 | 1216