



## ▶ Model 401 | Strobe Beacon

### FEATURES

- Powerful 5-joule power supply
- Fresnel lens directs light where needed and fills entire dome
- Proven components and technology
- Reverse polarity and voltage spike protection
- Protected against moisture and contaminants
- RFI Suppression
- Impact-resistant polycarbonate dome
- Protected against shock and vibration
- Corrosion resistant materials

### APPROVALS

- Meets SAE J1318 Class 3 specifications

#### **Model 401**

This low profile strobe works in multiple voltages (12–48 VDC) without requiring any modifications or adjustments. It is protected against reverse polarity and voltage spikes. The 401 strobe features a rubber base that resists corrosion and absorbs harsh shock. This 5-joule, double flash strobe is also available with a magnetic mount that includes cord and cigarette lighter plug adaptor. This strobe meets SAE J1318 Class 3 specifications.



**Specify Model**

- 220300 401 strobe, double flash
- 220308 401 strobe, double flash, with magnetic mount kit

**Accessories and Kits**

- 210387 Wiring kit, one strobe
- 210376 Wiring kit, two strobes
- 8107230 Flash tube
- 2005191 12-48 VDC power supply, double flash
- 601501-02 Amber dome
- 601501-03 Blue dome
- 601501-04 Red dome
- 601501-05 Clear dome
- 601501-06 Green dome

**Specifications**

Flash Rate	65/min.
Voltage	12-48 VDC
Amp Draw	0.65@12V to 0.17@48V
Power	5.4W
Joules	5J

**Physical Specifications**

Height	5.0 in (127 mm)
Diameter	5.9 in (150 mm)

**Ship Weight**

- 1.3 lbs (0.59 kg)
- 1.9 lbs (0.86 kg) w/magnet



210387



210376

