


Utility

products



Lightbars and Mini-Lightbars

Legend® CLASS 1 CAC Title 13

- Federal Signal's patent pending ROC (Reliable Onboard Circuitry™), technology eliminates approximately 85% of the potential failure points found in a typical lightbar
- Newly optimized Solaris® LED lights maximize warning signals at 360-degrees and 90-degrees off-axis
- Models available with serial communication and 6-button or 3-button controllers for ease of installation
- Five-year LED product warranty



Model	Description
LGD24-00107	24" Model with 3-Button Controller (10) amber LED modules, amber domes, permanent mount
LGD45-00845	45" Model with 6-Button Controller (18) amber LED modules, amber domes, flat mount
LGD45S-00007	45" Model discrete wire with on/off switch control (16) amber LED modules, amber domes, permanent mount
LGD53-00570	53" Model with 6-Button Controller (22) amber LED modules, amber domes, flat mount


AMBER DOME



LGD24-00107


AMBER DOME

AMBER DOME



LGD45-00845

AMBER DOME




LGD45S-00007

AMBER DOME

AMBER DOME

AMBER DOME



LGD53-00570

HighLighter® LED CLASS 1

- Features patented ROC (Reliable Onboard Circuitry™) LED technology
- Innovative Solaris® LED reflector design with uniform 360-degree light distribution
- Over 20 user selectable flash patterns; Magnet Select™ feature allows switchable flash patterns using a magnet
- Synchronized feature via bottom access panel; multiple LED units and LED perimeter lights
- Built-in permanent, magnetic and suction-cup magnetic mounts all in the existing HighLighter footprint
- Five-year LED product warranty



Model	Description
	Permanent Mount
454201-02	Amber LED with amber lens
454201-25	Amber LED with clear lens
	Suction-cup Magnet Mount — includes cigarette lighter plug with on/off switch
454200-02	Amber LED with amber lens
454200-25	Amber LED with clear lens
	Bracket Options
210883	Self-leveling bracket
454217	Riser mount bracket



210883
Self-Leveling Bracket



454217
Riser Mount Bracket

CLASS 1 CAC Title 13

HighLighter® and HighLighter® Strobe

- Three mounting options: permanent mount, magnetic mount and suction-cup mount
- Raised base makes installation and maintenance quick and easy
- 15" compact size
- Available in halogen or strobe models
- Five-year rotator warranty



Model	Description
	Halogen, Permanent Mount
450112-02	Amber dome, diagonal mirror, 12 VDC, 95 FPM, (2) rotators
450152-02	Amber dome, diagonal mirror, 12 VDC, 120 FPM, (2) rotators
451112-02	Amber dome, diagonal mirror, 12 VDC, 175 FPM, (2) rotators
	Halogen, Magnetic Mount-includes 10' cord and cigarette lighter plug with on/off switch
452142-02	Amber dome, diagonal mirror, 12 VDC, 95 FPM, (2) rotators
	Halogen, Suction-cup Magnetic Mount-includes 10' cord and cigarette lighter plug with on/off switch
450142-02	Amber dome, diagonal mirror, 12 VDC, 95 FPM, (2) rotators
	Strobe, Permanent Mount
453201-02	Amber dome, diagonal mirror, 12 VDC, 40W, (2) strobe heads
453001-02SB	Amber dome, diagonal mirror, 12 VDC, 20W, (2) strobe heads



450112-02, 452142-02,
452142-02



450152-02



451112-02

MicroEscape LED CLASS 1

- Solaris™ reflector technology and built-in Intelli-Flash LED flasher
- Fresnel dome optics produce a full dome of light
- Two operating modes with ten selectable flash patterns per mode
- Permanent Mount Kit included- no additional hardware is required



Model	Description
	Permanent Mount
ME4QL-A	9" Amber dome, (4) amber LED reflectors, 12 VDC
ME4QL-C-A	9" Clear dome, (4) amber LED reflectors, 12 VDC

Single Warning Beacons

UltraStar™ LED **CLASS 1**

- LEDnode™ technology for zero-maintenance lighting; no bulbs or strobe tubes to replace
- J-Bolt mount option
- Ten selectable "strobing" flash patterns
- Completely potted electronics
- SAE J1318 Class 1
- Five-year LED product warranty



252650-02SB

Model	Description
252650-02	Amber, 12-24 VDC, permanent/1" pipe mount

Pulsator® LED **CLASS 1** **CLASS 2**

- LEDnode™ technology for zero-maintenance lighting; no bulbs or strobe tubes to replace
- Ten selectable "strobing" flash patterns
- Flash completely fills dome; no dark spots or shadows
- SAE J845 Class 1 (212660-02)
- SAE J845 Class 2 (212650-02)
- Five-year LED product warranty



212660-02

Model	Description
	Permanent Mount
212660-02	Class 1, 12-24 VDC, amber
212650-02	Class 2, 12-24 VDC, amber

Model 651 Utility Light **CLASS 2**

- Low profile, aluminum base beacon
- SAE J1318 Class 2 Approved
- Five-year product warranty on strobe models and five-year LED warranty on LED models



420213-02

Model	Description
Strobe Model 651	12 J, 16W, 12-48VDC, double flash
420208-02	UTILITY LIGHT, blackout lens, Clear dust cover and polycarbonate mounting base, Amber
420213-02	UTILITY LIGHT, blackout lens, Clear dust cover, branch guard and aluminum 1" pipe/flush mount bottom, Amber
LED Model 651	
420222-02	UTILITY LIGHT, blackout lens, clear dust cover, branch guard, Amber LED, Amber dome
420223-02	Open style bottom, Amber LED, Amber dome

Model 951 **CLASS 1** **CAC Title 13**

- Automatic adjustment function at any voltage from 12-24 VDC
- Open-style aluminum base beacon
- Attached dust cover
- SAE J1318 Class 1 and CAC Title 13, Article 22
- Five-year product warranty



211749

Model	Description
211754	Utility light, high profile, double flash, 18J, 21.3W, 12-48 VDC, hi/low, black out lens, branch guard, aluminum 1" pipe/flush mounting base
211749	High profile, double flash, 18J, 21.3W, 12-48 VDC, hi/low, aluminum 1" pipe/flush mounting base
211746	High profile, quad flash, 18J, 21.3W, 12-48 VDC, hi/low, aluminum 1" pipe/flush mounting base

Single Warning Beacons

UltraStar™ US5 CLASS 1

- High- and low-profile strobe beacon
- Automatic adjustment to function at any voltages from 12-24 VDC
- SAE J1318 Class 1
- Five-year product warranty

Model	Description
	Permanent Mount
250121-02	13J, 18.4W, 12-24 VDC, double flash, tall dome, amber
251121-02	13J, 18.4W, 12-24 VDC, double flash, short dome, amber



251121-02

250121-02

UltraStar™ US6 CLASS 1

- High-profile, die-cast aluminum base strobe beacon including dust cover
- Automatic adjustment to function at any voltages from 12-24 VDC
- SAE J1318 Class 1
- Five-year product warranty

Model	Description
	Permanent Mount
252600-02	17/12 J, 21.3/15 W, 12-24 VDC, double flash
	Magnetic Mount
252601-02	17/12 J, 21.3/15 W, 12-24 VDC, double flash



252600-02

Model 100 CLASS 1 CAC Title 13

- Powerful 80,000 candelas halogen rotator that draws only 4.3 amps
- Rotator "floats" on a neoprene washer to absorb vibrations
- SAE J845 Class 1
- Five-year product warranty

Model	Description
	Permanent Mount
442112-02	12 VDC, 175 FPM, amber dome
443112-02	12 VDC, 95 FPM, amber dome
443312-02	12 VDC, 95 FPM, replacement bulb, amber dome
442114-02	24 VDC, 175 FPM, amber dome



442112-02

Directional/Interior Warning Lights

Viper EXT SignalMaster™ CLASS 1

- High output Solaris LED reflector technology
- Fully encapsulated waterproof modules
- Wide angle lens for better off-axis warning

Model	Description
320842	20", (4) lamp, 15 ft cable
320862	31", (6) lamp, 30 ft cable
320882	42", (8) lamp, 30 ft cable
320892	51", (8) lamp, 30 ft cable



320862

SignalMaster™ Plus CLASS 2

- Individually sealed LED modules with wide-angle lens
- Sturdy aluminum extrusion
- Internal or external mounting applications

Model	Description
SMLED-PLS-6	28", (6) LED modules, 50 ft cable, clear lens, amber LEDs
SMLED-PLS-8	37", (8) LED modules, 50 ft cable, clear lens, amber LEDs



SMLED-PLS-8

Directional/Interior Warning Lights

LED SignalMaster™



320792

- Patterns built by sequentially activating amber lamps; each lamp remains lit until the pattern is complete
- Available patterns include: left, right, center-out and flashing warning
- Resistant to heavy shock and high vibration
- Five-year product warranty

Model	Description
320772	42" Model with 15' cable Amber, (8) lamp SignalMaster
320782	42" Model with 30' cable Amber, (8) lamp SignalMaster
320786	42" Model with 60' cable Amber, (8) lamp SignalMaster
320792	51" Model with 30' cable Amber, (8) lamp SignalMaster
320793	51" Model with 50' cable Amber, (8) lamp SignalMaster
330312	Systems available-SignalMaster with Controller 320782 SignalMaster and 331105 Controller



320310



320330



320350

Halogen SignalMaster™

CAC Title 13



320172

- Patterns built by sequentially activating amber lamps; each lamp remains lit until the pattern is complete
- Available patterns include: left, right, center-out and flashing warning
- Resistant to heavy shock and high vibration

Model	Description
320172	41.8" Model with 15' cable Amber, (8) lamp SignalMaster
320182	41.8" Model with 30' cable Amber, (8) lamp SignalMaster
320192	41.8" Model with 50' cable Amber, (8) lamp SignalMaster
322112	Systems available-SignalMaster with Controller 320182 SignalMaster and 331105 controller
322122	320192 SignalMaster and 331105 controller
322612	51" light with 30' cable and 331105 controller



320310



320330



320350

SignalMaster™ Controllers



330104



331105

- Combined 12 or 24 VDC operation from one controller
- One controller operates (2) 4-, 6- or 8-lamp lights
- Tactile membrane switch panel
- Operates two halogen or multiple LED SignalMaster directional lights (SMC5)
- Brighter halogen patterns
- Fourteen warning patterns (SMC5); seven warning patterns (SMC1)
- AUX IN and AUX OUT functions with eight warning patterns and steady-on mode allows customization of complete warning packages (SMC5)
- Turn signal override feature (SMC5)
- Reliable surface mount circuitry

Model	Description
330104	SMC1 basic directional light controller
331105	SMC5 full-featured directional light controller

Perimeter Warning Lights

IMPAXX™ CLASS 2

- Advanced Solaris® LED reflective light technology
- Fully encapsulated waterproof housing
- Wide variety of synchronized patterns
- Five-year LED product warranty



IPX302-2

Model	Description
IPX300-2	Clear lens, advanced off-axis lens Amber, (3) high output LEDs
IPX302-2	Colored lens, advanced off-axis lens Amber, (3) high output LEDs
IPX310-2	Colored lens, advanced off-axis lens Amber, (3) high output LEDs
IPX312-2	Clear lens, center focused light output Amber, (3) high output LEDs

Viper® EXT CLASS 1 CAC Title 13

- Advanced Solaris® LED reflective light technology
- Fully encapsulated waterproof housing
- Wide angle lens for better off-axis warning
- Five-year LED product warranty



VPX802-2


Model	Description
VPX800-2	Clear off-axis lens Amber, (8) high powered LEDs
VPX802-2	Colored off-axis lens Amber, (8) high powered LEDs

CAC Title 13 Approved Models, (7) built-in approved flash patterns

VPX813-2	Clear off-axis lens Amber, (8) high powered LEDs
VPX814-2	Amber off-axis lens Amber, (8) high powered LEDs

SignalTech™ LED Lights

- Reflector cell technology enhances brightness and reduces sunlight washout
- Enhances lens design for uniform pattern
- Solid-state components are potted to withstand rugged road conditions



607123-02

607105-04

Model	Description
607123-02	Random Flashing Light Kits, 12-24V, 71 quad FPM
607101-02	Amber, 4" round (PAR 36) kit Amber, 6" oval kit
607100-04	STT, Turn, and Back-up LED Light Kit Models, 12-24V
607102-02	Red, 4" round STT
607124-05	Amber, 4" round, turn
607105-04	White, 4" round back-up light
607106-02	Red, 6" oval STT
607125-05	Amber, 6" oval turn
607125-05	White, 6" oval back-up light

Perimeter Warning Lights

QuadraFlare® 7"x 3" LED

- Advanced Solaris® LED reflective light technology in an industry standard 7x3 shape
- Superior off-axis lighting performance
- A variety of industry approved flash patterns
- All models include built-in flasher
- Five-year LED product warranty



QL73XFC-A

Model	Description
QL73XFC-A	Clear lens, amber LEDs
QL73XF-A	Amber lens, amber LEDs

QuadraFlare® 6"x 4" LED

- Advanced Solaris® LED reflective light technology in an industry standard 6x4 shape
- Built-in flasher featuring a variety of selectable patterns
- Five-year LED product warranty



QL64XF-A

Model	Description
QL64XF-A	Amber lens, amber LEDs
QL64XFC-A	Clear lens, amber LEDs

QuadraFlare® 9"x 7" LED CLASS 1 CAC Title 13

- Advanced Solaris® LED reflective light technology in an industry standard 9x7 shape
- Fully encapsulated waterproof housing
- Wide variety of synchronized patterns
- Five-year LED product warranty



QL97XF-A

Model	Description
QL97XF-A	Amber lens, amber LEDs
QL97 XFC-A	Clear lens, amber LEDs

Perimeter Warning Lights

Silver Series™ Remote Strobe System

- Four channel power supply
- Seven selectable flash patterns and dual light head cut-off feature
- Potted cavity resists moisture and vibration
- Compact size; mount virtually anywhere
- Three-year product warranty



Model	Description
Pre-configured Strobe System Models	
416127	SS4A power supply system with AMP connectors, (4) clear corner strobes, (2) 16' and (2) 30' cables
416129	SS4A power supply system with AMP connectors, (4) clear corner strobes, (4) 16' cables
Power Supply Models (one channel per strobe head required)	
416109	SS4A, four-channel
Strobe Head Models	
601103-02	Oval, amber, AMP connector
602111-02	Amber tube corner strobe

Area Lighting

Wireless VisiBeam®

- Ergonomically designed wireless transmitter operates over 100 ft
- Up to (4) transmitters programmable to operate (1) light
- "Gradual start" enables pinpoint light beam placement
- Continuous 360-degree horizontal and 140-degree vertical adjustment



Model	Description
Permanent Mount	
620200	12 VDC, 100W, wireless control
Magnetic Mount with cigarette lighter plug	
620200	12 VDC, 100W, wireless control

VisiBeam® II

- Operated by handheld remote control with an indicator light to show when the spotlight is in use
- Adjusts 105-degrees up and 35-degrees down from horizontal and rotates a full 360-degrees
- "Gradual start" enables pinpoint placement of light beam
- Velcro and "snap holder" mount included to mount control when not in use



Model	Description
Permanent Mount	
620122	12 VDC, 100W
Magnetic Mount with cigarette lighter plug	
620152	12 VDC, 100W

Area Lighting

Tractor and Utility


- High powered halogen beam
- Resistant construction reduces damage to bulbs
- Heavy gauge metal brackets



Model	Description
325541	Rectangle work lamp, sealed beam, flood pattern

9" x 7" Scene Lights

- Available in halogen or LED models
- Surface mounted LED models
- LED models feature Solaris reflector technology
- Industry standard mounting dimensions



QL97HSCENE



QL97LEDSCENE

Model	Description
QL97HSCENE	Area light, halogen
QL97LEDSCENE	Area light, LED, surface mount

Back-up Alarms

Evacuator® and Specialty Alarms

- Alarms have a wide range of decibel and voltage options
- Solid-state design protects and resists the effects of vibration
- Sealed unit protects internal components from moisture and contaminants



210502



210331

Model	Description
	Evacuator Model
210339	Single-function, 12-24 VDC, 97 dB
	Evacuator Plus Models
210330	Dual-function, 12-48 VDC, 87 dB
210331	Dual-function, 12-48 VDC, 97 dB
210333	Dual-function, 12-48 VDC, 107 dB
210335	Dual-function, 12-48 VDC, 112 dB
	Reactor Model
210502	107 dB and 112 dB (manually adjustable), 12-24 VDC

Mobile Camera Systems

- All cameras are high-resolution, color Sony CCD cameras
- TFT-LCD color monitors available in 5.6" or 7.0"
- Most cameras equipped with automatic day/night sensor and infrared LEDs for night vision
- Multiple camera cable lengths available
- Digital Video Recorder (DVR) with video and audio feed available
- Wide operating temperature range for all cameras: -22°F to 149°F
- Multi-voltage capability (12/24 VDC)
- Two-year limited warranty



Model	Description
	Systems
CAMSET56-NTSC-2	5.6" Monitor with two-camera input, (1) standard rear-view camera, (1) 65.5-ft extension cable
CAMSET70-NTSC4B	7.0" Monitor with four-camera input, (1) standard rear-view camera, 65.5-ft extension cable
	Monitors
CAMLCD-70	7.0" TFT-LCD monitor
CAMLCD-INT-56	5.6" TFT-LCD monitor with two-camera input integrated control box without split-screen capability
CAMLCD-INT-70B	7.0" TFT-LCD monitor with four-camera input integrated control box with split-screen capability
	Cameras
CAMCCD-REARNTSC	Standard rear-view CCD camera with night vision and audio, NTSC compatible
CAMCCD-SIDENTSC	Side-view CCD camera with night vision and audio, NTSC compatible
CAMCCD-FLSHNTSC	Bullet/Flush-mount CCD camera, NTSC compatible
CAMCCD-BALLNTSC	Ball CCD camera with night vision and audio, NTSC compatible
CAMCCD-DOMENTSC	Dome CCD camera with night vision and audio, for indoor use only, NTSC compatible
	Cables
CAMCABLE-5	5-m/16.5-ft camera-to-monitor extension cable
CAMCABLE-10	10-m/33-ft camera-to-monitor extension cable
CAMCABLE-15	15-m/49-ft camera-to-monitor extension cable
CAMCABLE-20	20-m/65.5-ft camera-to-monitor extension cable
CAMCABLE-40	40-m/131-ft camera-to-monitor extension cable
CAMCABLE-TRK	Truck/trailer cable set
	Accessories or Kits
CAMDVR-4-B	Digital video recorder
CAMADP-EXT	Camera cable adapter for connecting (2) extension cables together
CAMADP-RCA-IN	System adapter for connecting external RCA monitor
CAMADP-RCA-OUT	System adapter for connecting external RCA input
CAMBRK-HD	Heavy-duty monitor mount
CAMCABLE-SHORT	Camera extension cable, 4"
CAMLCD-BRACKET	Mounting bracket, monitor
	Common Replacement Parts
CAMADP-INT-2	Replacement wiring harness
CAMADP-INT-4	Replacement wiring harness



CAMCCD-FLSHNTSC



CAMCCD-SIDENTSC



CAMCCD-REARNTSC



CAMCCD-DOMENTSC
(indoor use only)



CAMCCD-BALLNTSC



Commercial Transportation Systems

Main Office / Factory

2645 Federal Signal Drive, University Park, IL 60484

Tel.: 800-824-0254 Fax: 800-787-6237

E-Mail: amberorders@fedsig.com

Web: www.fedsig.com

All others indicated are trademarks of Federal Signal Corporation.

©2011 Federal Signal Corporation. Printed in U.S.A.

M13000 I 511

