

# GPC 2150 with Welder, AC Generator, Air Compressor and Auto Idle



## GPC 2150 with Welder, AC Generator, Air Compressor and Auto Idle

### Dimensions

- Unit with fuel tank: 20"W x 53.5"D x 25"H, 640 lbs.
- Unit footprint without fuel tank and control box: 20"W x 48"D

### Product Description

Same as Goodall® Power Center 2050 plus Auto Idle. Idles the engine down when not under load.

### Engine

Electric start, air cooled Kohler Command OHV V-Twin

### DC Welding

DC Stick 40 – 250 amp – 225 amp 60% duty cycle

### Cables

25 ft. 1/0 ga. welding cables included

### AC Power

6000 watt 60 hz (while not welding), Synchronous, brushless, AC generator

Outlets

- one 120 volt, 20 amp duplex outlet
- one 120 volt, 30 amp twist lock outlet

- one 240 volt, 20 amp twist lock outlet

### Air Power

- 2 stage 24 CFM @ 100 psi, 150 psi max
- Air gauge on control panels monitors air tank pressure
- Air tank required, sold separately. See options.

### Control Panel

Plug and play feature of control panel for easy remote mounting. Requires extension harness for mounting distances beyond 12"

### Installation

- Provides for a compact, easy installation in less time with these simple bolt-in packages
- Center point lift included for easy installation
- Includes 8 gallon fuel tank (removable)
- Control panel box is removable for remote mounting

### Options & Accessories

- 950-0806 ft. Control Panel Harness
- 950-08112 ft. Control Panel Harness
- 950-15518 ft. Control Panel Harness
- 350-08750 ft. Welding Cable Upgrade
- 61-13030 gallon Vertical Mount Air Tank
- 61-13130 gallon Horizontal Mount Air Tank
- 50-44312 gallon Horizontal Mount Air Tank
- 990-200Factory installed stand and 30 gallon Air Tank Kit