

11-923 Start•All® with Air Compressor



11-923 Start•All with Air Compressor

Output

12/24 volt, 700/400 amp, 23 CFM @ 100 psi, 150 psi max

Dimensions

30"W x 40.5"D x 21"H, 475 lbs.

Engine

Electric start, air cooled Kohler V-twin OHV gasoline engine. Fuel tank required, sold separately

Cables & Clamps

30 ft., 1/0 ga. welding cable allows flexibility and ease of use, 1000 amp full-power clamps allow higher amperage flow

General Features

- Electric start, air cooled Kohler OHV V-twin gasoline engine. Fuel tank required, sold separately
- Single stage air compressor. 23 CFM @ 100 psi, 150 psi max. Air tank required, sold separately
- 30 ft., 1/0 ga. welding cable allows flexibility and ease of use
- 1000 amp full-power clamps allow higher amperage flow
- Voltage Control provides regulated voltage that is safe for vehicles and on-board electronics
- Reverse Current Shutdown Protection eliminates expensive repairs to the Start•All® if the unit runs out of gas
- Reverse Polarity Protection will not allow the Start•All® to be turned on if the cables are not hooked up correctly
- Polarity and low battery LED indicators confirm proper connections
- Anti-zap surge protection provides safer boosting
- Volt and amp meter to monitor boosting output
- Single DC boosting switch for easy operation