

62-200 Pressure Washer Gasoline Direct Drive



Part

62-200

Dimensions

43"W x 30"D x 41"H, 428 lbs.

Engine

- Performance proven engine with low oil protection and recoil start
- 404cc Subaru OHC engine
- 1.7 gallon fuel tank

Pump

- Direct drive triplex piston AR pump with ceramic plungers
- Stainless steel and brass unloader with adjustable pressure
- Forged brass manifold
- Thermal relief valve
- Low pressure detergent injection

Frame

- Reinforced powder coated steel tube frame with center balanced lifting hook
- Powder coated steel hose reel mounting brackets
- Wand holder
- Solid steel threaded axle
- 4 Pneumatic tires with tubes for longer life
- Locking tire brake

Components

- High quality gas filter/water separator ensures clean gas supply
- Complete system diagnostic board
- On/Off burner switch
- Pressure and high limit safety controls
- No. 1 or No. 2 diesel or kerosene fired burner
- Polyethylene burner fuel tank
- Easy coil drain helps prevent freezing in cold weather
- Energy efficient top-fired powder coated heat exchanger designed for convenient trouble shooting and easy maintenance
- Burner fuel cap 5.5 gallons
- Burner fuel cons 2.14 gph

Units Include

- 50 ft. x 3/8" steel wire braided pressure hose with screw connects, swivel and bend restrictors
- Professional grade insulated trigger gun with safety lock off
- Adjustable pressure insulated dual lance with 15° fixed and detergent nozzle

Miscellaneous

- Temperature rise 150°F/66°C above ambient, maximum outlet temperature is 200°F