

THIS SERIES IS DESIGNED FOR MAXIMUM PERFORMANCE AND RELIABILITY. THESE UNITS HAVE BECOME THE PRESSURE WASHERS OF CHOICE FOR CONTRACTORS WHO NEED GREAT RESULTS WITH COMPLETELY MOBILE UNITS.

62-200 PRESSURE WASHER

Gasoline Direct Drive

A great hot-water pressure washer. Does not need a 12 volt battery to operate the burner. The top-fired heat exchanger is designed for easy maintenance.

Engine

- Performance proven engine with low oil protection and recoil start
- 404cc Subaru OHC
- 1.7 gal. fuel tank

Pump

- Direct drive triplex piston AR pump with ceramic plungers
- Stainless steel and brass unloader valve
- Forged brass manifold
- Thermal relief valve
- Low pressure detergent injection

Frame

- Reinforced powder coated steel tube frame with center balanced lifting hook
- Powder coated steel hose reel mounting brackets
- Wand holder
- Solid steel threaded axle
- 4 pneumatic tires with tubes for longer life
- Locking tire brake

Component

- High-quality gas filter/water separator ensures clean gas supply
- Complete system diagnostic board
- On/off burner switch
- Pressure and high-limit safety controls
- No. 1 or No. 2 diesel or kerosene fired burner
- Polyethylene burner fuel tank
- Easy coil drain helps prevent freezing in cold weather
- Energy-efficient top-fired powder coated heat exchanger designed for convenient trouble shooting and easy maintenance



62-200

Unit Includes:

- 50' x 3/8" steel wire braided pressure hose with screw connects, swivel and bend restrictors
- Professional-grade insulated trigger gun with safety lock off
- Adjustable pressure insulated dual lance with 15° fixed and detergent nozzle

Miscellaneous

- Temperature rise 150° F / 66° C above ambient, maximum outlet temperature is 200° F

MODEL	62-090	62-092	62-100	62-120	62-140	62-160 (BELT DRIVE)	62-200 (HOT WATER DIRECT DRIVE)
PSI	1,000	1,500	2,700	3,000	4,000	4,000	3,500
GPM	2	2	2.3	2.4	3.5	3.4	3.3
ENGINE	187cc Honda	187cc Honda	187cc Honda	196cc Honda	404cc Subaru	404cc Subaru	404cc Subaru
DIMENSIONS	37" x 21" x 24.5"	37" x 21" x 24.5"	37" x 21" x 24.5"	37" x 21" x 24.5"	40" x 22.5" x 24.5"	39.5" x 28.5" x 26"	43" x 30" x 41"
NET WEIGHT	75 lbs.	75 lbs.	75 lbs.	85 lbs.	142 lbs.	195 lbs.	428 lbs.
BURNER FUEL CAP.	-	-	-	-	-	-	5.5 gal.
BURNER FUEL CONS.	-	-	-	-	-	-	2.14 gph

For shipping weight, add 40 lbs.



62-090



62-090 PRESSURE WASHER

Electric Direct Drive

- 1.5 hp engine, 120 volt, 1Ø, 12.5A
- 1,000 psi, 2 gpm
- Variable high/low pressure nozzle with adjustable spray pattern
- 25' x 3/8" non-marking hose with quick connects and swivel

- Professional-grade insulated trigger gun with safety lock-off
- 36" two-piece insulated lance
- 1-year electric motor limited warranty, 7-year pump warranty

62-092



62-092 PRESSURE WASHER

Electric Direct Drive

- 2.0 hp engine, 120 volt, 1Ø, 17.0A
- 1,500 psi, 2 gpm
- Variable high/low pressure nozzle with adjustable spray pattern
- 25' x 3/8" non-marking hose with quick connects and swivel

- Professional-grade insulated trigger gun with safety lock-off
- 36" two-piece insulated lance
- 1-year electric motor limited warranty, 7-year pump warranty

62-100



62-100 PRESSURE WASHER

Gasoline Direct Drive

- 160cc Honda OHC
- 2,700 psi, 2.3 gpm
- Quick-connect nozzles (15°, 25° and detergent nozzle)
- 25' x 3/8" wire braided pressure hose

- Professional-grade insulated trigger gun with safety lock-off
- 36" lance with rubber grip
- 1-year Honda engine limited warranty, 1-year pump warranty

62-120



62-120 PRESSURE WASHER

Gasoline Direct Drive

- 196cc Honda OHC
- 3,000 psi, 2.4 gpm
- Quick-connect nozzles (15°, 25° and detergent nozzle)
- 25' x 3/8" wire braided pressure hose

- Professional-grade insulated trigger gun with safety lock-off
- 36" lance with rubber grip
- 1-year Honda engine limited warranty, 1-year pump warranty

62-140



62-140 PRESSURE WASHER

Gasoline Direct Drive

- 404cc Subaru OHC
- 4,000 psi, 3.5 gpm
- Quick-connect nozzles (0°, 15° and 25°)
- 50' x 3/8" non-marking hose with quick connects, swivel and bend restrictors

- Professional-grade insulated trigger gun with safety lock-off
- 48" lance with rubber grip
- 3-year Subaru engine limited warranty, 7-year pump warranty

62-160



62-160 PRESSURE WASHER

Gasoline Direct Drive

- 404cc Subaru OHC
- 4,000 psi, 3.4 gpm
- Quick-connect nozzles (0°, 15°, 25°, 40°)
- 50' x 3/8" non-marking hose with quick connects, swivel and bend restrictors

- Professional-grade insulated trigger gun with safety lock-off
- 48" lance with rubber grip
- 3-year Subaru engine limited warranty, 7 year pump warranty

MODEL OPTIONS

62-301 High Pressure Detergent Injection

62-302 Low Pressure Detergent Injection