

The Stinger 2020 is the next evolution in work-ready flashlights and produces 2,000 lumens. Its aluminum alloy body with an anti-roll design is ergonomically shaped for a sure grip. It features dual power switches and an intuitive mode selector switch for ease of use. Its long-lasting lithium-ion battery pack offers multiple charging options: battery USB port and battery bank charger or existing Stinger<sup>®</sup> smart chargers and bank charger.



Four operating modes:	7.67" (19.48 cm); 12.3 oz (350g)			
- High for a high lumen beam: 2,000 lumens; 315m beam; runs 2 hours	Limited Lifetime Warranty Visit streamlight.com for full warranty information			
- Medium for bright light & longer run time: 850 lumens; 200m beam; runs 4 hours				
- Low for extended run time: 100 lumens; 70m beam; runs 24 hours	#78100 Stinger 2020 - Light only - Black			
- Strobe for disorienting or signaling: runs 3.25 hours	#78101 Stinger 2020 - 120V AC/12V DC 1 holder - Black			
	#78102 Stinger 2020 - 230V AC/12V DC 1 holder - Black			
Aluminum alloy body with ergonomic, anti-roll body design and textured grip	#78103 Stinger 2020 - 240V AC/12V DC 1 holder - Black			
	#78104 Stinger 2020 - 12V DC 1 holder - Black			
IPX7 waterproof; 2m impact resistance tested	TAA Compliant			




**PRODUCT FACT SHEET** 

## STINGER® 2020 RECHARGEABLE FLASHLIGHT

	MARKET				
	APPLICATIONS:	Law Enforcement, Sporting Goods, Security, Fire & Rescue, Hardware/Tool, Automotive, Industrial, Consumer.			
	DESCRIPTION:	Compact & extremely powerful, the Stinger <sup>®</sup> 2020 features 2000 lumens, an independent intensity selector switch and <b>a "finger grip" for an enhanced grip.</b> In addition, it has a body switch and tail cap tactical on off switch and a battery status indicator. The Stinger <sup>®</sup> 2020 Li-Ion USB rechargeable battery packs can be charged inside or outside the flashlight.			
	CASE MATERIAL:	Premium quality Aluminum Alloy body and non-slip rubberized comfort side panels, available in black.			
	DIMENSIONS:	Length: 7.67 in. (19.48 cm) Diameter: Major Diameter: 1.62 in. (4.11cm)			
	WEIGHT:	12.3 oz. (350 grams) with battery packs.			
	LENS:	High temperature, shock mounted, impact resistant Borofloat $^{\circ}$ glass, gasket sealed.			
	LIGHT SOURCE:	High power LED, white, impervious to shock with a 50,000 hour lifetime.			
	LIGHT OUTPUT:	See Chart. Optimized electronics provide regulated intensity. Deep-dish parabolic reflector produces a concentrated beam with optimum peripheral illumination.			
	ON/OFF/INTENSITY:				
	RUN TIME:	See Chart. All claims to 10% of initial lumen output. Strobe: 3.25 continuous hours.			
	BATTERY:	Two (2) Streamlight® SL-B26™ protected Li-Ion USB rechargeable battery packs with on-board safety control circuit, 2600mAh, rechargeable up to 500 times.			
	CHARGE HOLDERS:	: Fits existing Stinger® chargers. Smart charger fully recharges within 8 hours (5V/1A USB input) or 6 hours (12VDC input).			
	CHARGE CORDS:	Streamlight <sup>®</sup> universal AC input voltage, 5V/1A USB or 12.7V/.8A output charge cords available with IEC Type A (US & Japan), Type C (Euro), Type G (UK) or Type I (Australia) plugs. 12VDC cigarette lighter or direct wire automotive cords. Streamlight <sup>®</sup> USB cord.			
		High power LED for extreme brightness. Ergonomic anti-roll body design with textured grip. Intensity slide switch indicates mode at a glance. Multiple charging options. IPX7 rated for water proof operation to 1 meter submersion. Not a dive light or for underwater use. Two (2) meter impact resistance tested. Serialized for positive identification. LED Charge-continuity indicator on charger base. Compact, snap-in charger mounts in any position.			
	WARRANTY:	ANTY: Streamlight's Limited Lifetime Warranty.			
	APPROVALS: CE Meets applicable European Community Directives.				
CEC Compliant TAA Trade Agreement Act-Compliant.					
					OPTIONAL ACCESSORIES:
		PERFORMANCE CURVE			
	OUTPUT	X4, 2,000 850 100			

	FLISIANDARD	nigh	MEDIOM	LOW
OUTPUT	342	2,000 LUMENS	850 LUMENS	100 LUMENS
RUN TIME	$\bigcirc$	2h	4h	24h
DISTANCE	K	315m	200m	70m
INTENSITY		25,000 cd	10,000cd	1,200cd



All performance claims to ANSI/PLATO FL1-2019 Standard All Rights Reserved. Borofloat® is a registered trademark by a company of the Schott group. Issued: 04/28/2020 Revised: 07/28/2020 Rev: 2 Assembled in USA