



all-Grip

VEHICLE RECOVERY SYSTEMS



HMPE 12 Strand Synthetic Rope Winch line

Major Advantages of Synthetic Ropes

- Equally strong to steel wire rope
- Significantly less weight
- Easier handling and flexible
- No sharp broken wires-safer on hands

PART NUMBER	SIZE	LENGTH	SELF-LOCKING EYE HOOK	WORKING LOAD LIMIT	BREAK STRENGTH	WEIGHT
PWL3850	3/8"	50 ft.	4020AS	4,400 lbs.	17,600 lbs.	5.5 lbs.
PWL3875	3/8"	75 ft.	4020AS	4,400 lbs.	17,600 lbs.	6.5 lbs.
PWL38100	3/8"	100 ft.	4020AS	4,400 lbs.	17,600 lbs.	7.5 lbs.
PWL71650	7/16"	50 ft.	4032AS	5,375 lbs.	21,500 lbs.	9.3 lbs.
PWL71675	7/16"	75 ft.	4032AS	5,375 lbs.	21,500 lbs.	10.3 lbs.
PWL716100	7/16"	100 ft.	4032AS	5,375 lbs.	21,500 lbs.	11.8 lbs.
PWL12100	1/2"	100 ft.	4032AS	7,650 lbs.	30,600 lbs.	12.3 lbs.
PWL12150	1/2"	150 ft.	4032AS	7,650 lbs.	30,600 lbs.	15.3 lbs.
PWL58250	5/8"	250 ft.	4054AS	11,875 lbs.	47,500 lbs.	32.2 lbs.
PWL34250	3/4"	250 ft.	4080AS	14,500 lbs.	58,000 lbs.	46.3 lbs.

Always use corner protectors!