

CENTURY®

THE NEXT GENERATION EXPRESS GEN II

For the professional operator who demands a durable auto-load unit for high volume towing without sacrificing the capabilities to handle tough light-duty recovery work, The Century Express Generation II provides the total answer in this all new high performance package.



With increased rear visibility, positive and negative power tilt with limiter switches, a low profile crossbar with recessed pins and redesigned jaws, the operator can quickly and easily hook up to most vehicles from the safety and comfort of the cab of the truck.



The Century Express Gen II features a hydraulic extendable recovery boom, twin lift cylinders, single or dual 8,000 lb. winches, along with passenger and driver side manual control stations provide the operator with recovery capabilities not usually found in most auto-load units.

STANDARD FEATURES

- Integrated Boom & Wheel Lift System
- Hydraulic Auto-load Crossbar
- In-Cab Remote Control Pendant on Cord with 8 Functions
- Dual Manual Controls
- 1 Pair of Safety Straps
- Safety Chains in Rear Pockets
- Tool Compartment, Left & Right Hand Side
- Adjustable Modular Body
- Power Boom Elevation with Holding Valve
- 8,000 lb. Variable Speed Hydraulic Winch (Dual Winches on the 312)
- 3/8" x 100' Cable Assembly
- 360° Directional Boom End Swivel
- Winch Cable Tensioner & Free Spool Handles
- Federal Standard #108 Lighting
- Wiring Harness with Junction Box
- Mud Flaps
- Tailboard Mounted D-Rings
- Back-Up Alarm
- Power Fold for Stinger Storage
- Self Centering Crossbar
- Roller Guided Hose Tracking System
- Positive and negative tilt with limiter stop switch

BOOM SPECIFICATIONS

Century 311/312 Express

Lift Height at Maximum Elevation

Retracted	78"
Extended	111"

Reach Past Tailgate

Minimum Elevation (Extended)	50"
Maximum Elevation (Extended)	22"

Boom Rating at Boom Swivel

Retracted	16,000 lbs.
Extended	4,000 lbs.



Optional 5th
wheel adapter easily
installs on the crossbar

WHEEL-LIFT SPECIFICATIONS

Retracted Distance from Tailgate

At Normal Tow Position 51"

Extended Distance from Tailgate

At Normal Tow Position 84 3/4"

Maximum Hydraulic Extension 33 3/4"

Lift Rating 4,000 lbs.

Tow Rating 7,500 lbs.

WINCH RATING & CABLE

Rating (first layer of drum) each Winch 8,000 lbs.

Diameter and Length (each winch) 3/8" x 100'

Type 6 x 19 Hemp Center, IPS

OPTIONAL FEATURES

- | | |
|--------------------------------|-----------------------------------|
| • Clutch Pump | • Trailer Ball Adapter |
| • Composite or Aluminum Body | • 5th wheel adapter |
| • Tow Sling | • Emergency Lighting |
| • Motorcycle Attachment | • Work Lights |
| • Aluminum Tubular Light Pylon | • Front Push Bumper |
| • Steel Light Pylon | • 24" Tunnel Toolbox for 84" C.A. |
| • Go-Jak Mounting Brackets | • Other Popular Century Options |

CHASSIS RECOMMENDATION

GVWR 15,000 - 19,000 lbs.

Minimum Cab to Axle (Clear) 60"

Maximum Cab to Axle (Clear) 84"

All ratings are based on structural factors only, not vehicle capacities or capabilities. Specifications shown are approximations and may vary depending on chassis selected. Miller Industries Towing Equipment Inc. reserves the right to change or modify product and or specifications without notice or obligation. Some equipment shown is optional.



8503 Hilltop Drive Ooltewah, TN 37363

800-292-0330 | 423-238-4171

Fax 423-238-5371 www.MillerInd.com

millier
INDUSTRIES

©2014 Miller Industries Towing Equipment Inc.

ZIP'S TRUCK
EQUIPMENT INC.
800-222-6047 www.zipps.com