



# LiftGuard Magnetic Sling Protectors



DICA's magnetic LiftGuard Sling Protectors provide cut protection from damage caused by contact with edges, corners, protrusions and abrasive surfaces. LiftGuard Sling Protectors help ensure OSHA and ASME compliance for edge and corner protection.

The magnetic sling protector won't move from its intended spot and is engineered to withstand and displace high pressures. LiftGuard is 1/7 the weight of steel and designed to protect both your loads and your slings.

## KEY FEATURES

- ▶ LiftGuard Protectors are magnetic, staying where you put them.
- ▶ Superior cut protection for synthetic slings.
- ▶ Can be used with all sling types, including synthetic, wire rope and chain slings.
- ▶ Helps ensure compliance with OSHA safety regulations and ASME standards.
- ▶ Made from a non-metallic, high performance cast nylon.



# LiftGuard Magnetic Sling Protectors

## Medium Duty



MODEL	OVERALL LENGTH (in)	MAX SLING WIDTH (in)	1" SLING CAPACITY (lbs)	MAX CAPACITY BASED ON MAX SLING WIDTH (lbs)	WEIGHT (lbs)
LG-6-3-90	6	4	12,500	50,000	1.25
LG-9-3-90	9	7	12,500	87,500	1.75
LG-12-3-90	12	10	12,500	125,000	2
LG-18-3-90	18	16	12,500	200,000	3

## Heavy Duty



MODEL	OVERALL LENGTH (in)	MAX SLING WIDTH (in)	1" SLING CAPACITY (lbs)	MAX CAPACITY BASED ON MAX SLING WIDTH (lbs)	WEIGHT (lbs)
LG-6-3-270 HD	6	4	12,500	50,000	5
LG-9-3-270 HD	9	7	12,500	87,500	7
LG-12-3-270 HD	12	10	12,500	125,000	9
LG-18-3-270 HD	18	16	12,500	200,000	13

## Beam & Plate Units



MODEL	OVERALL LENGTH (in)	MAX SLING WIDTH (in)	1" SLING CAPACITY (lbs)	MAX CAPACITY BASED ON MAX SLING WIDTH (lbs)	WEIGHT (lbs)
LG-9-2-360G-0.5 (1 in Groove)	9	7	12,500	43,750	2.75

