



REVISION HISTORY		
REV.	DESCRIPTION	DATE
01	PRELIMINARY RELEASE PER LM13214	2013-10-28
Α	INITIAL RELEASE PER LM13214	2013-12-12

SPECIFICATIONS

1. CERTIFICATIONS:

Note: Unique components, accessories, and hardware kits are not typically Included in the Product Certification Test Protocols. Unless otherwise Specified, the Product Certifications referred to herein are predicated upon the base product model configuration.

- 2. LUMINOUS FLUX: 4500 lumens
- 3. ILLUMINANCE: lux
- 4. PEAK BEAM INTENSITY: Candela
- 5. EFFICACY: 67.9 lm/W
- 6. CORRELATED COLOR TEMPERATURE: K
- 7. VOLTAGE (NOMINAL): 12 to 24 VDC
- 8. VOLTAGE (EXTREME): 10 to 30 VDC
- 9. CURRENT (PEAK): 4.8A (@ 12 VDC NOMINAL)
- 10. POWER (MAXIMUM): 66.3W (@ 12 VDC NOMINAL)
- 11. TEMPERATURE RANGE: -22°F (-30°C) TO 122°F (50°C)
- 12. CONNECTION: 2 CONDUCTOR CABLE
- 13. MOUNTING: BRACKET MOUNT
- 14. HOUSING MATERIAL: ALUMINUM
- 15. LENS MATERIAL: POLYCARBONATE
- 16. PRODUCT WEIGHT: 5.5 LBS (2.48 Kg)

NOTES: 1. DIMENSIONS IN INCHES[MILLIMETERS (FOR REFERENCE)]

NON DISCLOSURE AGREEMENT

THIS DRAWNING AND THE DESIGN IT DISCLOSES ARE THE PRIVATE PROPERTY OF ECCO. AND IS ISSUED IN CONFIDENCE FOR ENGINEERINGAINFORMATION ONLY. THE DRAWNING AND / OR DESIGN MAY HOR BLISED, COPPIDE PREPODUCED, OR OTHERWISE DESCLOSED IN FOR AS A WHOLE TO OUTSIDESS OR USED FOR ANY OTHER PURPOSE WITHOUT THE PRIOR WRITTEN CONSENT OF ECCO. THE DRAWNING IS SUBJECT TO RECALL AT ANY TIME. YOUR POSSESSION OF THIS DOCUMENT CONSTITUTES ACCEPTANCE OF THESE TERMS, © 2013 ECCO.

