










The "Working Load Limit" is the maximum load in pounds which at any time or under any condition should ever be applied to a sling.

ALLOY CHAIN WORKING LOAD LIMITS — 4 TO 1 DESIGN FACTOR							
CHAIN SIZE (IN)	90°	60°	45°	30°	60°	45°	30°
							
	SINGLE LEG	DOUBLE LEG / SINGLE BASKET			TRIPLE & QUAD LEG / DOUBLE BASKET		
1/4 (9/32)	4,300	7,400	6,100	4,300	11,200	9,100	6,400
5/16	5,700	9,900	8,100	5,700	14,800	12,100	8,500
3/8	8,800	15,200	12,400	8,800	22,900	18,700	13,200
1/2	15,000	26,000	21,200	15,000	39,000	31,800	22,500
5/8	22,600	39,100	32,000	22,600	58,700	47,900	33,900
3/4	35,300	61,100	49,900	35,300	91,700	74,900	53,000
7/8	42,700	74,000	60,400	42,700	110,900	90,600	64,000
1	59,700	103,400	84,400	59,700	155,100	126,000	89,550
1 1/4	90,400	156,600	127,800	90,400	234,900	191,700	135,600

For choker hitch with minimum 120 degrees angle of choke, WLL must be reduced by 20%, except when using the Crosby A-1338 Cradle Grab Hook.