

CENTURY[®]

10 & 15 Series Carriers



At Century, we feel that "Keeping up with the Industry" is nothing but an excuse. If we can't produce a product that is superior to everything in it's class... then you won't see our name on it. Our Car Carriers are a perfect case-in-point. They possess every standard feature that you would expect from a World Leader, brought together in a sleek, attractive, and durable package. With an independent wheel lift system, positive lock down, extra low loading angle, and easy one-man operation, Century Carriers have driven past every limitation that has held "The Industry" in check. Century leaves no room for argument.



**"The Number One Selling Brand of Towing
& Recovery Equipment Worldwide."**

STANDARD FEATURES

Platform Available in Aluminum or Steel
Consolidated Tilt & Full Length Mounting Frame
Full Length Nylatron Slide Pads
Two 3" Lift Cylinders
One Extension Cylinder
Right and Left Front Chain Trays
Front and Rear Tie Down Slots
Positive Bed Lock Down System
Bed Anti-Tilt Feature
Adjustable Landing Legs
Removable Side Rails (15 Series Steel)
Solid Tube Side Rails (Aluminum and 10 Series Steel)
8,000 lb. Hydraulic Winch with 50' of Cable
Winch Clutch Release
Winch Roller Guides
Winch Cable Tensioner
Left and Right Hand Illuminated Controls
Back Up Lights
Federal Standard 108 Lighting
Back Up Alarm
Hydraulic Independent Wheel Lift System with Slide-In L-Arms
Wheel Lift Safety Pin
Safety Chains
Century Mud Flaps
Hydraulic Pump
Full Height Steel Headboard
Steel Beds Painted in Black Acrylic Urethane
Pre-Assembled and Factory Tested

OPTIONAL FEATURES

PTO
Galvanized Subframe
Optional Steel or Aluminum Tool Compartments
Switch Panel
Light Bar
Work Lights (Rear or Winch Mounted)
Spotlights (Directional)
Various Chain & Strap Assemblies
Additional Key Slots
Removable Tube Side Rails (N/A on Right Approach)
Removable Blade Side Rails (N/A on Right Approach)
Aluminum Overlay Side Rails (Steel Only, N/A on Right Approach)
Smooth Floor instead of Diamond Plate (Steel Only)
Apitong Wood Floor (N/A on Right Approach)
Additional Cross Members (Steel Only)
Optional Colors, Top of Deck & Removable Rails (Steel Only)
Right Approach Option (Steel 10 Series Only)
Body Built 102" Wide
3-Way Pivoting L-Arm System
Dock Stabilizer in lieu of Wheel Lift
Side Mount Winch
Planetary Winch in lieu of Worm Gear Winch
10,000 lb. or 12,000 lb. Winch
Lanyard Control for Winch
Stationary Headboard
Factory Installation
Many other Popular Century Carrier Options

BED

SPECIFICATIONS	10 SERIES	15 SERIES
Platform Length	19', 19'6", 21', & 22'	19', 21', & 22'
Load Rating	*10,000 lbs.	*15,000 lbs.
Platform Thickness	3/16" Aluminum or Steel	3/16" Aluminum or Steel
Steel Crossmembers	2" x 2" on 8" Centers	2 1/2" x 2 1/2" on 8" Centers
Aluminum Crossmembers	2 5/16" on 4" Centers	3" on 4" Centers
Overall Width	96"	96"
Inside Width	91.5"	91.5"
Controls	5 Spool Mono-block Valve	5 Spool Mono-block Valve
Winch Rating (1st Layer)	8,000 lb.	8,000 lb.
Cable Diameter and Length	3/8" x 50'	3/8" x 50'

* Platform rating is based on equally distributed load.

WHEEL-LIFT SPECIFICATIONS

Lift Rating at Full Extension	3,000 lbs. <small>(2,000 lbs. for under 19,000 GVW)</small>	3,500 lbs.
Tow Rating at Full Extension	6,250 lbs. <small>(5,000 lbs. for under 19,000 GVW)</small>	6,250 lbs.

TRUCK RECOMMENDATIONS

Minimum GVW	15,000	25,500
Maximum GVW	25,500	28,000
Recommended Tire Size	16" - 19.5"	22.5"
Minimum Height from Ground to Top of Frame	34"	40"
Maximum Height from Ground to Top of Frame	39"	44"

RECOMMENDED CAB TO AXLE (C.A.)

19'	120"
19'6"	127"
21'	144"
22'	156"

NOTE: Specifications subject to change without notice. All ratings are based on structural factors only, not vehicle capacities or capabilities.

CENTURY®

8503 Hilltop Drive • Ooltewah, TN 37363
800-292-0330 • 423-238-4171
FAX 423-238-5371 • www.MILLERIND.com

DISTRIBUTED BY:



316 West Milwaukee - P.O. Box 511 - New Hampton, IA 50659
1-800-222-6047 - (641) 394-3166 - www.zips.com