
EYE SLIP HOOK GRADE 30/43

WORKING LOAD LIMIT: 2,600 TO 20,200 LBS.

BENEFITS & FEATURES

- Hooks are heat treated and tempered
- Design factor 4:1 when used with Grade 30
- Design factor 3:1 when used with Grade 43
- When using these hooks with Grade 30 chain, the assembly must be rated to the working load limit of the chain.
- Hook embossed with trace code providing traceability through manufacturing and testing process to heat of steel
- Not to be used for overhead lifting





| Size (in.) | Working Load Limit (lbs.) | Standard Package | Product Code | | | | Dimensions (in.) | | | | | | | |
|---------------|---------------------------------|---------------------|-------------------------------------|------------------------------------|-----------------------------|-----------|------------------|------|-----------------------|--------------------|------|------|------|------------------|
| | | | Self Colored (without Latch)* | Zinc Plated (without Latch)* | Zinc Plated (with Latch) | Latch Kit | w | D | H without latch | H with latch | L | R | G | Weight (lbs.) |
| 1/4 | 2,600 | 50 | - | 75193 | 75143 | 75199 | 0.53 | 2.47 | 0.81 | 0.73 | 3.69 | 2.61 | 0.81 | 0.38 |
| 5/16 | 3,900 | 50 | 74294 | 75293 | 75243 | 75199 | 0.69 | 2.88 | 0.83 | 0.82 | 3.98 | 2.70 | 0.91 | 0.57 |
| 3/8 | 5,400 | 50 | _ | 75393 | 75343 | 75299 | 0.78 | 3.25 | 0.92 | 0.93 | 4.11 | 3.17 | 1.13 | 0.83 |
| 7/16 | 7,200 | 10 | _ | 75493 | _ | _ | 0.91 | 3.73 | 1.23 | - | 5.28 | 3.64 | 1.31 | 1.38 |
| 1/2 | 9,200 | 10 | _ | 75593 | 75543 | 4X410 | 1.03 | 4.25 | 1.30 | 1.21 | 6.13 | 4.20 | 1.50 | 1.95 |
| 5/8 | 13,000 | 5 | 74694 | 75693 | - | - | 1.28 | 5.23 | 1.69 | - | 7.41 | 5.11 | 1.81 | 3.72 |
| 3/4 | 20,200 | 5 | _ | 75793 | _ | _ | 1.53 | 6.28 | 2.45 | _ | 8.88 | 6.00 | 2.34 | 3.72 |

^{*} Hooks without latches are not designed for latches to be added.



CHAIN & RIGGING ATTACHMENTS (CMRP-6)

PHONE: 800.888.0985 WWW.CMWORKS.COM