



LI-ION BATTERY BANK CHARGER

MARKET

APPLICATIONS: Fire, Sporting Goods, Law Enforcement, Industrial, Automotive, Security, Consumer

DESCRIPTION: The Streamlight® Li-Ion Battery Bank Charger is designed to individually charge and maintain up to eight (8) Streamlight® Li-Ion USB rechargeable battery packs. The Streamlight® Li-Ion Battery Bank Charger is available with eight (8) Li-Ion USB rechargeable battery packs and is also available without battery packs.

CASE MATERIAL: Impact resistant engineered polymer housing available in black.

DIMENSIONS: Length: 10.45 in (26.54 cm) Width: 4.75 in. (12.06 cm) Height: 1.00 in (2.54 cm)

WEIGHT: 7.61 oz. (216 grams) 20.88 oz. (592 grams) with eight (8) battery packs

BATTERY: Streamlight® SL-B26™ protected Li-Ion USB rechargeable battery pack with on-board safety control, rechargeable up to 500 times.

CHARGER INPUT: 120VAC or International power supply wall adapter or 12 VDC direct wire with 2.5mm barrel plug are available to connect with the charger.

CHARGE TIME: 5.25 hours to charge one battery pack or multiple battery packs.
Green and red LED charge indicator for quick visual notification of charge status.

FEATURES: Charger temperature safety circuit prevents damage to battery packs while charging.

WARRANTY: Streamlight's Limited Lifetime Warranty.

APPROVALS:  Meets applicable European Community directives.

 CEC compliant.

NFPA Meets requirements of NFPA 1901-14.1.10.2 (2016) mounted in upright position.

OPTIONAL ACCESSORIES: N/A