

STAR HEADLIGHT & LANTERN CO.









240C

240SF

Specifications and Features

- Star X-Fire[™] technology
- 12 different selectable flash patterns in either of two phases, plus steady-on
- Exceeds SAE Class I J845 standards
- S-Link System™ synchronizing capabilities with other Star LED units, hardwire only
- · Extremely low current draw
- RFI protection
- · Rugged die-cast base is fully gasketed
- Permanent mount, 1" pipe mount, flange mount, magnet mount

- Dimensions: short lens 4 1/4"H x 5 1/2"Dia., tall lens - 6"H x 5 1/2"Dia.
- Voltage: permanent 12-24V DC, magnet 12V DC
- Amp draw: 2 amps @ 12V DC
- Lens color:
- Approvals: SAE Class I (Amber short and tall)

Model Numbers/Descriptions:

| 240C | LED beacon, tall lens, permanent mount |
|-------|---|
| 240CF | LED beacon, tall lens, flange mount |
| 240CM | LED beacon, tall lens, magnet mount |
| 240S | LED beacon, short lens, permanent mount |
| 240SF | LED beacon, short lens, flange mount |
| 240SM | LED beacon, short lens, magnet mount |

SF001 Rev B 7-19-2018





Star Headlight & Lantern Co., Inc. 455 Rochester Street Avon, NY 14414 Phone: 585-226-9500

starheadlight.com

Fax: 888-478-2797

