



SUPERSPRINGS™ LIMITED WARRANTY

Your SuperSprings™ product is covered by the **Limited Warranty** explained below that gives you specific legal rights. This Limited Warranty is the only warranty made in connection with your leaf spring suspension stabilizer. SuperSprings™ neither assumes nor authorizes any vendor, retailer or other person or entity to assume for it any other obligation or liability in connection with this product or Limited Warranty.

WHAT IS COVERED? Subject to the terms, exclusions and limitations herein, SuperSprings International, Inc. Warrants to the initial retail or fleet purchaser only that its SuperSprings™ leaf spring suspension stabilizer shall be free of defects in material and workmanship for:

**Five (5) years when used in non-commercial applications; or
One (1) year when used in commercial applications.**

This Limited Warranty extends only to the initial retail or fleet purchaser with respect to use upon the vehicle the SuperSprings™ product is first installed. The term of Limited Warranty shall be measured from the date of purchase. SuperSprings™ reserves the rights to: (a.) require claimant's proof of purchase as a condition of this Limited Warranty, (b.) make future revisions to its Limited Warranty without prior notice. As used herein, "commercial applications" means any vehicle intended, licensed or used (partially or otherwise) in connection with commerce and shall include but not be limited to "Commercial Motor Vehicles" as defined or intended by the U.S. Code of Federal Regulations. *ALL OTHER EXPRESS OR IMPLIED WARRANTIES INCLUDING MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE ARE HEREBY DISCLAIMED.*

WHAT IS NOT COVERED. Your **Limited Warranty** does not cover any damage arising or related to any vehicle, product, or component combination other than the SuperSprings™ suspension stabilizer. Your SuperSprings™ Limited Warranty further does not cover vehicles, products or components supplied by us or others that SuperSprings International, Inc determines to have been damaged by or subjected to:

- Vehicle use in excess of GVWR combined vehicle weights/ tow ratings or other OEM design specifications or limitations.

SuperSprings®

Warranty Card

To activate your SuperSprings product warranty please complete and return this form today with a copy of your receipt for the item(s) purchased. Completed forms may be faxed or mailed to the number or address listed below.

Buyer Information

Name

Street Address

City

State

Zip

Phone

Fax

Email Address

Item Purchased

Purchase Date

Seller Information

Company Name

Phone Number

Sales Invoice #

Installation Information

Vehicle Make

Vehicle Model

Vehicle Year

Please note: Without a copy of your receipt this warranty information CANNOT be processed.

Please ensure you have attached a copy of your SuperSprings purchase receipt with this completed form


Please mail to SuperSprings address listed below.

Comments:



Self-Adjusting Suspension Stabilizers

Independent tests showed SuperSprings improve driving control by 29%



Installation Instructions

For easy installation, you will need to:

- READ ALL the instructions completely before beginning.
- Have the necessary tools available

Tools required:

- 1 – 1 1/16" wrench / socket
- 1 – 1 1/8" wrench / socket
- 1 – Sturdy Clamp or SuperSprings Installation tool (for SSA22~SSA25 heavy duty installation)

SAFETY NOTICE: WE RECOMMEND THAT THIS INSTALLATION BE DONE BY A PROFESSIONAL OR PERSONS WITH SOUND MECHANICAL KNOWLEDGE.

SUPERSPRINGS are designed to work in conjunction with original equipment (factory) springs only. Please consult SuperSprings factory (866-898-0720) if original springs have been replaced with an after-market product.

WARNING: These instructions are meant to be a general guide for installing SuperSprings. SuperSprings International assumes no liability for the actual installation process. Consumers should apply common automotive safety practices when raising and working on any vehicles. Do NOT put yourself in a position where if the vehicle should move unexpectedly, you may be seriously hurt. SuperSprings are designed to improve vehicle carrying capacity and road handling. Do NOT load any vehicle beyond the manufacturer's specifications.

LIMITED WARRANTY

See separate warranty information page.

SuperSprings International Corporation
5055 Sixth Street, Carpinteria, CA 93013
Support: 866-898-0720
Support Email: gerry@supersprings.com
Web: www.supersprings.com

PLEASE NOTE:

Remember to ensure brake cables are not touching the SuperSprings blade(s). Secure them out of the way with zip ties or re-routing. Also, avoid all air conditioning lines, fuel filler hoses and emergency brake lines / cables.