

HOLMES

600 R

"16 Ton Rotator"



Some Optional Equipment May Be Shown.

Holmes opens up a whole new dimension in medium duty towing and recovery with the Holmes 600R. A recovery boom with 16 tons of retracted capacity and 6 tons of extended capacity that rotates 220° makes this the most versatile unit yet from the oldest and most trusted name in the industry. The underlift with 89" of reach easily handles a wide range of vehicles from autos through trucks. Visit your local Holmes distributor to learn how the Holmes 600R can increase your bottom line.



STANDARD FEATURES

- 120" Aluminum Modular Body with 3 Compartments per side
- Lift Fork Storage & Chain Rack, Passenger & Driver side
- Manual Control Stations, Driver & Passenger side
- Passenger side Lanyard Control for Underlift & Recovery Boom
- Front Outriggers with Hydraulic Up & Down Feature and Pivot Pad
- Rear Outriggers with Hydraulic Up & Down Feature and Pivot Pad
- Mud flaps
- 3 sets of Lift Forks
- Rubber Fenderettes
- Safety Chains
- Door Closures
- Federal Standard 108 Lighting
- LED Body Lighting
- Dual Hydraulic Pump
- 6,000 lb. "L" Arms with Pivoting Receivers
- "D" Rings
- Tool Compartment Lighting
- Spring Loaded Cable Tiebacks



OPTIONAL FEATURES

- Airshift PTO
- Light Bar
- LED Smart Lights Kit
- In-Cab Controls
- Additional Lifting Attachments
- Installation
- Underlift Tailboard Controls
- 24" or 36" Aluminum Saddle Box
- Work Lights
- Light Pylon
- Wide Load Light Bar
- Air & Electrical Hookups
- Chain Kits
- Wireless Controller

CHASSIS RECOMMENDATIONS

- GVWR 27,000 to 31,000 lbs.
- Maximum Frame Height 38"
- Cab to Axle (clear) Required 120"
- Tire Size Maximum 275/70 R 22.5

WRECKER SPECIFICATIONS

- Retracted 30° 32,000 lbs.
- Extended 30° 12,000 lbs.
- Maximum Angle 47°
- Maximum Hook Height 212"
- Reach Past Tailboard At 30° & Full Extension 56 1/2"
- Boom Rotation 210°

UNDERLIFT SPECIFICATIONS

- Fully Retracted (with Forks) 12,000 lbs.
- Fully Extended (with Forks) 8,500 lbs.
- Extended or Retracted with "L" Arms 6,000 lbs.
- Underlift Reach to Center of Fork Holder Extended 89"
- Underlift Reach to Center of Fork Holder Retracted 48"
- Positive Tilt 20°
- Negative Tilt 8°

WINCH SPECIFICATIONS

- Planetary Winches 15,000 lbs.
- Cable 1/2" x 150' 6 x 37 IWRC
- Spring Cable Tensioner & Air Free Spool

NOTE: Specifications subject to change without notice. All ratings specified are based on structural factors only, not vehicle capacities or capabilities.



Proven Design & Technology



DISTRIBUTED BY:

