

ULTRASTINGER® LED
HIGH LUMEN LONG RANGE RECHARGEABLE FLASHLIGHT
MARKET
APPLICATIONS: Law Enforcement, Sporting Goods, Security, Fire & Rescue, Hardware/Tool, Automotive, Industrial, Consumer

DESCRIPTION: 1,100 lumens of blinding light coupled with 65,000 candela for a far reaching beam, the UltraStinger® LED is the newest and brightest addition to the Stinger® series. The UltraStinger® LED offers 3 microprocessor controlled variable intensity modes, strobe mode and the latest in high powered LED technology. In addition the UltraStinger® LED also offers three different user selectable programs.

CASE MATERIAL: 6000 series machined aircraft aluminum with non-slip rubberized comfort grip.

DIMENSIONS: Length: 11.82 in. (30 cm) Diameter: Major Diameter: 2.37 in. (6.01 cm)
Body Diameter: 1.19 in. (3 cm)

WEIGHT: 19.9 oz. (564 grams) with battery (included in purchase)

LENS: Unbreakable polycarbonate with scratch-resistant coating. O-ring sealed.

LIGHT SOURCE: High power LED, white, impervious to shock with a 50,000 hour lifetime.

LIGHT OUTPUT: See Chart. Optimized electronics provides regulated intensity. Custom "Total Internal Reflection" optic for narrow beam and optimum peripheral illumination.

ON/OFF: Multi-function, easy access head mounted push-button switch designed for extremely long life; tested at 1 million actuations. TEN-TAP® programmable switch allows user selection of one of three different programs: High/medium/low with strobe (factory default), high only without strobe, or high/medium/low without strobe.

RUN TIME: See Chart. All claims to 10% of initial lumen output. Strobe: 3 hours 15 minutes.

BATTERY: 5-cell, 6 Volt, 2.6Ahr Ni-MH sub-C battery, rechargeable up to 1000 times.

CHARGE HOLDERS: Fits existing Stinger® chargers and new Smart chargers.
Steady charger: Fully recharges in 16 hours.
Smart charger: Fully recharges within 7.5 hours (5V/1A USB input) or 4.5 hours (12VDC input).

CHARGE CORDS: Streamlight universal AC input voltage, 5V/1A USB or 12.7V/.8A output charge cords available with IEC Type A (US & Japan), Type C (Euro), Type G (UK) or Type I (Australia) plugs. 12VDC cigarette lighter or direct wire automotive cords.





FEATURES:

 High power LED for extreme brightness.
 IPX4 Rated for water resistant operation.
 3 meter impact resistance tested.
 LED Solid State Power Regulation provides maximum light output throughout battery life.
 TEN-TAP® programmable switch allows user to select one of three different programs.
 Serialized for positive identification.
 LED Charge-continuity indicator on charger base.
 Compact, snap-in charger mounts in any position.

WARRANTY: Streamlight's Limited Lifetime Warranty.

APPROVALS: CE Meets applicable European Community Directives.
 BC CEC Compliant (Smart charger models only)

OPTIONAL ACCESSORIES: Safety wands, ring holder, 5-Unit Bank Charger, Fast Charger

	FL 1 STANDARD	HIGH	MEDIUM	LOW
OUTPUT		1,100 LUMENS	350 LUMENS	90 LUMENS
RUN TIME		1h 30min	4h 30min	16h
DISTANCE		510m	290m	141m
INTENSITY		65,000cd	21,000cd	5,000cd

