

PRO-LOK

Why Use Anything Else?



A031

M.C.O.T. Button Lifter Tool

The A031 Button Lifter is a variation of the MCOT™ (Multi-Car Opening Tool.)

To use the A031, expose precision ground tip by removing the protective rubber cap during use. Gently wedge the weatherstrip away from the window glass, creating a gap for insertion of the tool (see photo 1.) Insert the A031 with the tip of the tool roughly in line with the vertical button head. Lower the tool down in the door cavity and rotate it beneath the bottom edge of the window glass. Lift the tool until the bridge contacts the inside weatherstrip.

Remove the wedges; releasing pressure between the weatherstrip and window glass, easing entry of the tool. An A033 Separator tool may also be used for applications with very tight inside weatherstrip. Continue to lift the tool, working the rounded “bridge” past the weatherstrip until the tip of the tool is inside the passenger compartment. It may be necessary to gently work the tool back and forth to work it past tight weatherstrip.

Once the tip is inside the vehicle, maneuver the tip against the button head. Twist the tool to grip the button and lift to unlock the door (see photo 2 & 3.) On buttons with a smooth surface, grip the button at the top, to avoid scratching.



GENERAL APPLICATIONS : *This tool works on vehicles equipped with raised vertical buttons found on some: ACURA, AUDI, BMW, CHEVROLET, FORD, GEO, LEXUS, MAZDA, MERCEDES, MITSUBISHI, PLYMOUTH, TOYOTA, VOLKSWAGEN, VOLVO and various other models.*