


PRO-LOK

Why Use Anything Else?



A042-LA & A042-LAXL
58" & 76" Long Arm Tools



These tools are intended for use on vehicles that have frameless windows or in which traditional vehicle entry methods no longer work. The tools must be used with A065 and A067 wedges. Gently insert the A065-A1 Wedge Starter and Window Protector at the top corner of the door frame/window glass. Insert the A065 into the space created by the A065-A1, between the door/window and the frame. Inflate Wedge. Insert the A067 into the gap created between the door/window and the vehicle on the vertical edge of the door/window. Press wedge firmly into the gap. Protect the edge of the glass and the paint of the inside door by inserting the A042-SL plastic sleeve between the door and the vehicle to avoid tool contact on the glass/paint. Carefully feed the A042-LA through the edge of the sleeve. Application 1 - Retrieve the key by inserting the tool into the passenger compartment and hooking onto the key ring. Carefully retrieve the keys. You may be able to thread them through the opening, read the code, or read cuts on the key. Application 2 - Activate the power unlock button by inserting the tool into the passenger compartment and depressing the unlock button on the console or door. Application 3 - Manipulate the manual locking lever. Application 4 - Access the pull handle (which opens the door when in the locked position) by inserting the tool and hooking the pull handle on door. Pull the tool towards you to unlock the door. Deflate and remove all tools before pulling the outside handle.



GENERAL APPLICATIONS: *This tool works on vehicles equipped with pull handles which you would access with an across the car type method.*