PRO-LOK Why Use Anything Else?

AO37

Button Finger Tool

The AO37 Button Finger Tool is a variation of the MCOT (Multi-Car Opening Tool.) Designed to open vehicles with vertical button linkage systems, it is especially effective on Toyota products, where other entry methods may be ineffective.

An AO33 Separator tool may also be used with the AO37 for applications with very tight inside weatherstrip. (see AO33 instructions)

To use the AO37, remove the protective rubber tip during use.

Gently wedge the weatherstrip away from the window glass, creating a gap for insertion of the tool (see photo 1.)

Insert the AO37 with the tip of the tool roughly in line with the vertical button head.

Lower the tool down in the door cavity and rotate it beneath the bottom edge of the window glass.

Lift the tool until the bridge contacts the inside weatherstrip.

Remove the wedge; releasing pressure between the weatherstrip and window glass, easing entry of the tool.

Continue to lift the tool, working the rounded "bridge" past the weatherstrip until the tip of the tool is inside the passenger compartment. It may be necessary to gently work the tool back and forth to work it past tight weatherstrip.

Once the tip is inside the vehicle, maneuver the tip against the button head. Twist the tool to grip the button and lift to unlock the door (see photos 2 & 3.) On buttons with a smooth surface, grip the button at the top, to avoid scratching.











GENERAL APPLICATIONS: This tool works on vehicles equipped with vertical buttons found on some: AUDI, CHEVROLET, FORD, GEO, ISUZU, LEXUS, MAZDA, MITSUBISHI, PLYMOUTH, TOYOTA, VOLKSWAGEN and various other models.