

5043 Farlin Ave. St. Louis, MO 63115 www.associatedequip.com 314-385-5178

45 Amp / 130 Amp Boost Wheel Charger & Power Supply for Standard Automotive, Deep-Cycle, AGM and Gel Cell batteries w/ Dead Battery Override Control

Specifications:

Model Number ESS6007B DC Output 45 Amps DC Leads 6½ft - 6.5AWG Clamp Rating 400A Limited Warranty Three Years Shipping Dimensions 23"x19"x16" Weight 47 LBS AC Cord / Voltage 6' 16-3 / 120VAC 60 Hz Battery Types 12 Volt Flooded,
DC Leads 6½ft - 6.5AWG Clamp Rating 400A Limited Warranty Three Years Shipping Dimensions 23"x19"x16" Weight 47 LBS AC Cord / Voltage 6' 16-3 / 120VAC 60 Hz
Clamp Rating 400A Limited Warranty Three Years Shipping Dimensions 23"x19"x16" Weight 47 LBS AC Cord / Voltage 6' 16-3 / 120VAC 60 Hz
Limited Warranty Three Years Shipping Dimensions 23"x19"x16" Weight 47 LBS AC Cord / Voltage 6' 16-3 / 120VAC 60 Hz
Shipping Dimensions 23"x19"x16" Weight 47 LBS AC Cord / Voltage 6' 16-3 / 120VAC 60 Hz
Weight 47 LBS AC Cord / Voltage 6' 16-3 / 120VAC 60 Hz
AC Cord / Voltage 6' 16-3 / 120VAC 60 Hz
60 Hz
Battery Types 12 Volt Flooded,
AGM, and Gel Cell
batteries - including
Spiral Cell, Orbital,
or Optima Batteries
Display Analog Meter and
3 LED display
indicating charge
status

Product Bulletin

MODEL ESS6007B



Features:

- Electrical Stability System (ESS™)
 technology turns ESS6007B into a stable
 power supply for extended service procedures
 or re-flashes. Nominal 13.7V DC Output
- Program for deep discharge recovery of flooded batteries
- Patented diagnostics indicate weak or defective battery
- Charges all types of 12 volt batteries.
- Designed for AGM, Gel Cell, Sealed, and Standard Flooded batteries including Spiral cell, OrbitalTM, or OptimaTM Batteries
- Dead Battery Override Control
- "Safe In Any Weather" Operation
- UL Listed
- MADE IN USA