



Case Material: High-impact ABS thermoplastic housing. Rubberized impact bumper, lens ring and cushioned-grip handle.

Dims/Weight: Length: 11.5 in. (29.2 cm) Width: 5.1 in. (13 cm) Height: 7 in. (17.8 cm) 7.9 lbs (3.58 kg) with battery (included in purchase)

Light Source: Six C4® LEDs, impervious to shock with a 50,000 hour lifetime. 6 wide pattern parabolic reflectors produce a smooth flood pattern. Optimized electronics provide regulated intensity. Jumper selectable high or low setting.

Output: High: 615 lumens; 4,000 candela; 126m beam; runs 8 hours  
Low: 330 lumens; 2,150 candela; 93m beam; runs 18 hours

Battery: Zero-maintenance 6V, 12Ah sealed lead acid battery. Red and green LEDs give charge status feedback.

Models: Standard System - International safety orange or high-visibility yellow; includes shoulder strap; includes AC/DC chargers and mounting rack; ideal for field maintenance, inspection of construction sites, and remote equipment.

Vehicle Mount System - International safety orange or high-visibility yellow; comes with vehicle-mountable hard-wire rack and shoulder strap.

Power Failure System - International safety orange or beige; includes AC/DC chargers and "smart" power failure circuitry that automatically illuminates the E-Flood LiteBox when the power goes off.

Features: • IPX4 Rated for weather resistant operation • LED Solid State circuitry provides regulated light output throughout battery life.  
• Serialized for positive identification. • Locking charge rack option

Approvals: Most models meet applicable European Community Directives

Charge rack meets requirements of NFPA 1901-14.1.11.2 (2003) mounted in any position.

Warranty: Streamlight warrants this product to be free of defects for a lifetime of use except for batteries and bulbs, abuse and normal wear. We will repair, replace or refund the purchase price of this product should we determine it to be defective. This limited lifetime warranty also excludes rechargeable batteries, chargers, switches and electronics which have a 2 year warranty with proof of purchase. THIS IS THE ONLY WARRANTY, EXPRESSED OR IMPLIED, INCLUDING ANY WARRANTY OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE. INCIDENTAL, CONSEQUENTIAL OR SPECIAL DAMAGES ARE EXPRESSLY DISCLAIMED EXCEPT WHERE SUCH LIMITATION IS PROHIBITED BY LAW. You may have other specific legal rights which vary by jurisdiction.

Item	UPC	Item #
E-Flood LiteBox Standard System - IEC Type C (230V) AC/12V DC - shoulder strap & mounting rack - Orange	080926-45802-4	45802
E-Flood LiteBox Standard System - IEC Type C (230V) AC/12V DC - shoulder strap & mounting rack - Yellow	080926-45822-2	45822
E-Flood LiteBox Standard System - IEC Type G (240V) AC/12V DC - shoulder strap & mounting rack - Orange	080926-45803-1	45803
E-Flood LiteBox Standard System - IEC Type G (240V) AC/12V DC - shoulder strap & mounting rack - Yellow	080926-45823-9	45823
E-Flood LiteBox Standard System - IEC Type A (120V) AC/12V DC, shoulder strap & mounting rack - Orange	080926-45801-7	45801
E-Flood LiteBox Standard System - IEC Type A (120V) AC/12V DC, shoulder strap & mounting rack - Yellow	080926-45821-5	45821
E-Flood LiteBox Standard System - IEC Type A (100V) AC/12V DC, shoulder strap & mounting rack - Orange	080926-45804-8	45804
E-Flood LiteBox Standard System - IEC Type A (100V) AC/12V DC, shoulder strap & mounting rack - Yellow	080926-45824-6	45824
E-Flood LiteBox Vehicle Mount System - 12V DC direct wire rack, shoulder strap - Orange	080926-45805-5	45805
E-Flood LiteBox Vehicle Mount System - 12V DC direct wire rack, shoulder strap - Yellow	080926-45825-3	45825
E-Flood LiteBox Power Failure System - IEC Type C (230V) AC/12V DC, mounting rack - Orange	080926-45808-6	45808
E-Flood LiteBox Power Failure System - IEC Type C (230V) AC/12V DC, mounting rack - Beige	080926-45818-5	45818
E-Flood LiteBox Power Failure System - IEC Type G (240V) AC/12V DC, mounting rack - Orange	080926-45809-3	45809
E-Flood LiteBox Power Failure System - IEC Type G (240V) AC/12V DC, mounting rack - Beige	080926-45819-2	45819
E-Flood LiteBox Power Failure System - IEC Type A (120V) AC/12V DC, mounting rack - Orange	080926-45807-9	45807
E-Flood LiteBox Power Failure System - IEC Type A (120V) AC/12V DC, mounting rack - Beige	080926-45817-8	45817
E-Flood LiteBox Power Failure System - IEC Type A (100V) AC/12V DC, mounting rack - Orange	080926-45810-9	45810
E-Flood LiteBox Power Failure System - IEC Type A (100V) AC/12V DC, & mounting rack - Beige	080926-45820-8	45820
E-Flood LiteBox (WITHOUT CHARGER) - Orange	080926-45806-2	45806
E-Flood LiteBox (WITHOUT CHARGER) - Beige	080926-45816-1	45816
E-Flood LiteBox (WITHOUT CHARGER) - Yellow	080926-45826-0	45826



Item	UPC	Part #	
DC2 direct wire charge cord	080926-22050-8	22050	
DC1 Charge Cord	080926-22051-5	22051	
IEC Type C (230V) AC charge cord	080926-22061-4	22061	
IEC Type A (100V/120V) AC charge cord	080926-22060-7	22060	
IEC Type G (240V) AC charge cord	080926-22062-1	22062	
Locking Device (keyed differently) *Must be factory installed	080926-40163-1	40163	
Quick Release Strap	080926-44050-0	44050	
Shoulder Strap	080926-45232-9	45232	
Standard System Mounting Rack	Orange	080926-45070-7	45070
Direct Wire 12V DC Mounting Rack	Orange	080926-45071-4	45071
Standard System Mounting Rack	Yellow	080926-45072-1	45072
Direct Wire 12V DC Mounting Rack	Yellow	080926-45074-5	45074
Mounting Rack (LiteBox)	Beige	080926-45073-8	45073
Sealed Lead Acid Battery	080926-45937-3	45937	
E-Flood Upgrade Kit	080926-45842-0	45842	

